

屋内照明器具特性	
品番 (品名)	NNN13600SK
光源	LDA7L-G/D/S/K6 ×1 810.0 lm
管理番号	K0179319 (1) DB1
BZ分類	BZ2/8.5/BZ1

器具効率		24 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z CM
保守率		良 中 否	0.63	0.6	16	14	12	11	16	13	12	11	15	13	12	11	15	13	12	11	11
			0.6	0.8	18	16	15	14	18	16	15	14	17	16	15	14	17	15	14	14	13
			0.56	1.0	20	18	17	16	19	18	16	16	19	17	16	15	18	17	16	15	15
			1.25	21	19	18	17	20	19	18	17	20	19	18	17	19	18	18	17	16	
下方投影面積		cm ²	1.5	22	20	19	18	21	20	19	18	21	20	19	18	20	19	18	18	17	
			2.0	22	21	20	20	22	21	20	20	22	21	20	19	21	20	20	19	19	
等価発光面積		cm ²	2.5	23	22	21	21	23	22	21	21	22	21	21	20	22	21	21	20	20	
			3.0	23	23	22	21	23	22	22	21	23	22	21	21	22	22	21	21	20	
H m	1.01 H m	1.39 H m	4.0	24	23	23	22	24	23	23	22	23	23	22	22	23	22	22	21	21	
			5.0	24	24	23	23	24	23	23	23	23	23	23	22	23	23	22	22	21	
			7.0	24	24	24	23	24	24	24	23	24	23	23	23	23	23	23	22	22	
			10.0	25	24	24	24	24	24	24	24	24	24	24	23	23	23	23	23	22	

