

屋内照明器具特性	
品番 (品名)	NNN15511
光源	LED4000_70_2660 ×1 2660.0 lm
管理番号	K0167806 (2) DR1
BZ分類	BZ7/0.7/BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		43 % 57 %	室指数	照明率 (X0.01) Z CM																	
保守率		良 中 否	0.63	0.6	48	35	28	22	44	33	26	21	37	29	23	19	31	24	20	16	11
			0.6	0.8	56	44	36	30	52	41	34	29	44	36	30	25	37	31	26	22	16
			0.56	1.0	62	51	43	37	58	48	40	35	49	41	35	31	41	35	30	27	19
				1.25	68	57	49	43	63	53	46	41	54	46	41	36	45	39	35	31	23
下方投影面積		cm ²	1.5	72	62	54	48	67	58	51	46	57	50	45	40	48	43	38	35	26	
等価発光面積		cm ²	2.0	77	69	62	56	72	64	58	53	62	56	51	47	52	48	44	40	30	
取付 高さ	器具間隔最大限		2.5	81	73	67	62	75	69	63	58	65	60	55	51	55	51	47	44	33	
	横方向 (A) 縦方向 (B)		3.0	83	77	71	66	78	72	67	62	67	62	58	55	57	53	50	47	36	
1.5m	1.99 m	2.14 m	4.0	87	81	76	72	81	76	72	68	70	66	63	60	60	57	54	52	40	
2	2.63	2.7	5.0	89	84	80	76	83	79	75	72	72	69	66	63	62	59	57	55	42	
2.5	3.27	3.27	7.0	91	88	84	81	86	82	79	77	74	72	70	67	64	62	60	58	45	
3	3.91	3.87	10.0	93	91	88	86	88	85	83	81	76	75	73	71	66	64	63	62	48	

