

屋内照明器具特性	
品番 (品名)	NNF 2 1 2 3 0 C
光源	LDL20S.N/11/12-K(960) ×1 960.0 1 m
管理番号	K0125039(0)DR1
BZ分類	BZ6/0.7/BZ5/8.5/BZ6

器具効率	97%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	3%	床	10%				10%				10%				10%				0%	
下方光束	94%	室指数	照明率 (X0.01)																ZCM	
保守率	良 0.81 中 0.77 否 0.68	0.6	52	40	32	27	51	39	32	27	48	38	31	26	46	37	31	26	24	
		0.8	62	50	42	36	60	49	41	36	57	47	40	35	54	46	40	35	32	
		1.0	68	57	49	43	66	56	48	42	63	54	47	42	60	52	46	41	39	
		1.25	74	63	56	50	72	62	55	49	68	60	54	49	65	58	52	48	45	
下方投影面積	c m ²	1.5	78	68	61	55	76	67	60	55	72	65	59	54	69	62	57	53	50	
		2.0	83	75	69	63	81	74	68	62	78	71	66	61	74	69	64	60	57	
取付高さ	器具間隔最大限		2.5	87	80	74	69	85	78	73	68	81	76	71	67	78	73	69	65	62
	横方向 (A)	縦方向 (B)	3.0	89	83	78	73	87	82	77	72	84	79	74	71	80	76	72	69	66
1.5m	2.01 m	1.91 m	4.0	93	87	83	79	91	86	82	78	87	83	80	76	84	80	77	75	71
2	2.67	2.51	5.0	95	90	86	83	93	89	85	82	89	86	83	80	86	83	81	78	75
2.5	3.33	3.12	7.0	97	94	91	88	95	92	89	87	92	89	87	85	89	87	84	83	79
3	4.02	3.74	10.0	99	96	94	92	97	95	93	91	94	92	90	88	91	89	88	86	83

