

# 屋内照明器具特性

品番 (品名)	NNLK41515 + NNL4600SWT														
光源	LED4000_85_6250 x1 6250.0 lm														
管理番号	K0135570 (2) DB1														
BZ分類	BZ4 / 1.8 / BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	4 %	室指数	照明率 ( X0.01 )															ZCM			
下方光束	96 %																				
保守率	良 中 否	0.83	0.6	5.9	4.7	4.0	3.4	5.7	4.6	3.9	3.4	5.4	4.5	3.8	3.4	5.2	4.4	3.8	3.3	3.1	
		0.81	0.8	6.8	5.7	5.0	4.4	6.6	5.6	4.9	4.4	6.3	5.4	4.8	4.3	6.0	5.3	4.7	4.3	4.0	
		0.77	1.0	7.4	6.4	5.7	5.1	7.2	6.3	5.6	5.1	6.9	6.1	5.5	5.0	6.6	5.9	5.4	4.9	4.7	
			1.25	8.0	7.0	6.4	5.8	7.8	6.9	6.3	5.8	7.4	6.7	6.1	5.7	7.1	6.5	6.0	5.6	5.3	
下方投影面積	c m <sup>2</sup>	1.5	8.4	7.5	6.8	6.3	8.2	7.4	6.8	6.3	7.8	7.1	6.6	6.2	7.5	6.9	6.4	6.1	5.8		
		2.0	8.9	8.2	7.6	7.1	8.7	8.0	7.5	7.0	8.3	7.8	7.3	6.9	8.0	7.5	7.1	6.8	6.4		
取付高さ	器具間隔最大限		2.5	9.2	8.6	8.1	7.6	9.0	8.4	8.0	7.5	8.6	8.2	7.7	7.4	8.3	7.9	7.5	7.2	6.9	
	横方向 (A)	縦方向 (B)	3.0	9.4	8.9	8.4	8.0	9.2	8.7	8.3	7.9	8.9	8.5	8.1	7.7	8.5	8.2	7.9	7.6	7.2	
1.5m	1.46 m	2.11 m	4.0	9.7	9.3	8.9	8.6	9.5	9.1	8.8	8.5	9.2	8.8	8.5	8.3	8.8	8.6	8.3	8.1	7.7	
2	1.94	2.65	5.0	9.9	9.5	9.2	8.9	9.7	9.4	9.1	8.8	9.4	9.1	8.8	8.6	9.0	8.8	8.6	8.4	8.0	
2.5	2.41	3.22	7.0	10.1	9.8	9.6	9.3	9.9	9.7	9.4	9.2	9.6	9.4	9.2	9.0	9.3	9.1	8.9	8.8	8.4	
3	2.89	3.81	10.0	10.3	10.1	9.9	9.7	10.1	9.9	9.7	9.6	9.8	9.6	9.5	9.3	9.4	9.3	9.2	9.1	8.7	

