

# 屋内照明器具特性

品番 (品名)	LGBZ6113														
光源	LED6200_70_3650 x1 3650.0 lm														
管理番号	K0164174(0)D 1														
BZ分類	BZ4														

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	21%																			
下方光束	79%																			
室指数	照明率 ( X0.01 ) ZCM																			
保守率	良 中 否 0.63 0.6 0.56	0.6	56	44	37	32	53	43	36	31	49	40	34	30	45	38	33	29	26	
		0.8	65	55	48	42	63	53	46	41	58	50	44	40	53	47	42	38	34	
		1.0	72	62	55	50	69	60	53	49	63	56	51	46	58	52	48	44	40	
		1.25	78	69	62	57	74	66	60	56	69	62	57	53	63	58	54	50	45	
下方投影面積	c m <sup>2</sup>	1.5	81	73	67	62	78	71	65	61	72	66	62	58	67	62	58	55	49	
		2.0	87	80	75	70	83	77	72	68	77	72	68	65	71	67	64	61	55	
取付高さ	器具間隔最大限		2.5	90	84	80	75	87	81	77	73	80	76	73	69	74	71	68	66	59
	横方向 (A)	縦方向 (B)	3.0	92	87	83	79	89	84	81	77	82	79	76	73	76	73	71	69	62
H m	1.21 H m	1.22 H m	4.0	95	91	88	85	92	88	85	82	85	82	80	77	79	77	75	73	66
			5.0	97	93	91	88	93	90	88	85	87	84	82	80	80	79	77	75	68
			7.0	99	96	94	92	95	93	91	89	89	87	85	84	82	81	80	79	71
			10.0	100	98	97	95	97	95	94	92	90	89	88	87	84	83	82	81	73

