

屋内照明器具特性	
品番 (品名)	XND5 5 3 9 WN
光源	LED5000_80_5505 ×1 5505.0 lm
管理番号	K0179590 (1) DB 1
B Z 分類	BZ1 / 3.5 / BZ2 / 8.5 / BZ1

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																	Z C M	
下方光束				1 0 0 %																		
保守率		良 中 否	0 . 7 6	0 . 6	7 1	6 3	5 7	5 3	7 0	6 2	5 7	5 3	6 9	6 1	5 6	5 3	6 7	6 0	5 6	5 3	5 1	
			0 . 7 2	0 . 8	8 1	7 3	6 7	6 3	7 9	7 2	6 7	6 3	7 7	7 1	6 6	6 3	7 6	7 0	6 6	6 3	6 1	
			1 . 0	8 6	7 9	7 4	7 0	8 5	7 8	7 4	7 0	8 3	7 7	7 3	7 0	8 1	7 6	7 2	6 9	6 8		
			0 . 6 4	1 . 2 5	9 1	8 5	8 0	7 6	8 9	8 4	8 0	7 6	8 7	8 2	7 9	7 6	8 5	8 1	7 8	7 5	7 3	
下方投影面積		c m ²	1 . 5	9 4	8 8	8 4	8 1	9 2	8 7	8 3	8 0	9 0	8 6	8 2	8 0	8 8	8 4	8 1	7 9	7 7		
等価発光面積			c m ²	2 . 0	9 7	9 3	8 9	8 6	9 6	9 2	8 9	8 6	9 4	9 0	8 8	8 5	9 2	8 9	8 6	8 4	8 2	
取付 高さ	器具間隔最大限		2 . 5	1 0 0	9 6	9 3	9 0	9 8	9 5	9 2	9 0	9 6	9 3	9 1	8 9	9 4	9 2	8 9	8 8	8 5		
	横方向 (A)		縦方向 (B)		3 . 0	1 0 1	9 8	9 5	9 3	1 0 0	9 7	9 4	9 2	9 8	9 5	9 3	9 1	9 5	9 3	9 2	9 0	8 8
H m	1 . 2 7 H m		1 . 2 7 H m		4 . 0	1 0 3	1 0 0	9 8	9 6	1 0 2	9 9	9 7	9 6	9 9	9 8	9 6	9 4	9 7	9 6	9 4	9 3	9 1
					5 . 0	1 0 4	1 0 2	1 0 0	9 8	1 0 3	1 0 1	9 9	9 8	1 0 1	9 9	9 8	9 6	9 8	9 7	9 6	9 5	9 2
					7 . 0	1 0 5	1 0 4	1 0 2	1 0 1	1 0 4	1 0 3	1 0 1	1 0 0	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 4
					1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 0	1 0 1	1 0 0	9 9	9 9	9 6

