

屋内照明器具特性	
品番 (品名)	XND5 5 6 7 WV
光源	LED3500_80_5210 ×1 5210.0 lm
管理番号	K0179661 (0) DB 1
B Z 分類	BZ1

器具効率		1 0 0 % 上方光束 0 % 下方光束 1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
			室指数	照明率 (X 0 . 0 1) Z C M																					
保守率		良 中 否	0 . 7 6	0 . 6	7 4	6 6	6 0	5 7	7 3	6 5	6 0	5 7	7 1	6 4	6 0	5 6	7 0	6 4	5 9	5 6	5 5				
			0 . 7 2	0 . 8	8 3	7 5	7 0	6 7	8 2	7 5	7 0	6 6	8 0	7 4	6 9	6 6	7 8	7 3	6 9	6 6	6 4				
			1 . 0	8 8	8 1	7 7	7 3	8 7	8 1	7 6	7 3	8 5	7 9	7 6	7 2	8 3	7 8	7 5	7 2	7 1					
			0 . 6 4	1 . 2 5	9 2	8 6	8 2	7 9	9 1	8 6	8 1	7 8	8 9	8 4	8 1	7 8	8 7	8 3	8 0	7 7	7 6				
下方投影面積		c m ²	1 . 5	9 5	9 0	8 6	8 2	9 3	8 9	8 5	8 2	9 1	8 7	8 4	8 1	8 9	8 6	8 3	8 1	7 9					
等価発光面積			c m ²	2 . 0	9 8	9 4	9 1	8 8	9 7	9 3	9 0	8 7	9 5	9 1	8 9	8 6	9 3	9 0	8 8	8 6	8 4				
取付 高さ	器具間隔最大限		2 . 5	1 0 0	9 7	9 4	9 1	9 9	9 6	9 3	9 1	9 7	9 4	9 2	9 0	9 5	9 2	9 0	8 9	8 7					
	横方向 (A) 縦方向 (B)		3 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 8	9 5	9 3	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 1	8 9					
H m	1 . 2 7 H m	1 . 2 7 H m	4 . 0	1 0 3	1 0 1	9 9	9 7	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 5	9 8	9 6	9 5	9 4	9 1					
			5 . 0	1 0 4	1 0 2	1 0 1	9 9	1 0 3	1 0 1	1 0 0	9 8	1 0 1	9 9	9 8	9 7	9 9	9 7	9 6	9 5	9 3					
			7 . 0	1 0 5	1 0 4	1 0 3	1 0 1	1 0 4	1 0 3	1 0 2	1 0 1	1 0 2	1 0 1	1 0 0	9 9	1 0 0	9 9	9 8	9 7	9 5					
			1 0 . 0	1 0 6	1 0 5	1 0 4	1 0 3	1 0 5	1 0 4	1 0 3	1 0 2	1 0 3	1 0 2	1 0 1	1 0 1	1 0 1	1 0 0	9 9	9 9	9 6					

