

屋内照明器具特性

品番 (品名)	NNLK41509 + NNL4506HNP														
光源	LED5000_85_4870 x1 4870.0 lm														
管理番号	K0135563 (0) DB 1														
BZ分類	BZ4 / 1.8 / BZ5														

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
		床	10 %				10 %				10 %				10 %				0 %	
上方光束	5 %	室指数																		
下方光束	95 %	照明率 (X0.01)																		
		ZCM																		
保守率	良	0.83	0.6	5.9	4.7	4.0	3.4	5.7	4.6	3.9	3.4	5.4	4.5	3.8	3.4	5.2	4.3	3.8	3.3	3.1
	中	0.81	0.8	6.8	5.7	5.0	4.4	6.6	5.6	4.9	4.4	6.3	5.4	4.8	4.3	6.0	5.3	4.7	4.3	4.0
	否	0.77	1.0	7.4	6.4	5.7	5.1	7.2	6.3	5.6	5.1	6.9	6.1	5.5	5.0	6.6	5.9	5.4	4.9	4.7
			1.25	8.0	7.0	6.3	5.8	7.8	6.9	6.3	5.8	7.4	6.7	6.1	5.7	7.1	6.5	6.0	5.6	5.3
下方投影面積		cm ²	1.5	8.4	7.5	6.8	6.3	8.2	7.4	6.8	6.3	7.8	7.1	6.6	6.1	7.5	6.9	6.4	6.0	5.7
等価発光面積		cm ²	2.0	8.9	8.2	7.6	7.1	8.7	8.0	7.5	7.0	8.3	7.7	7.3	6.9	8.0	7.5	7.1	6.7	6.4
取付高さ	器具間隔最大限		2.5	9.2	8.6	8.1	7.6	9.0	8.4	7.9	7.5	8.6	8.1	7.7	7.4	8.3	7.9	7.5	7.2	6.9
	横方向 (A)	縦方向 (B)	3.0	9.4	8.9	8.4	8.0	9.2	8.7	8.3	7.9	8.9	8.4	8.1	7.7	8.5	8.2	7.8	7.6	7.2
1.5m	1.46m	2.1m	4.0	9.7	9.3	8.9	8.5	9.5	9.1	8.8	8.4	9.2	8.8	8.5	8.2	8.8	8.5	8.3	8.0	7.7
2	1.93	2.65	5.0	9.9	9.5	9.2	8.9	9.7	9.4	9.1	8.8	9.4	9.1	8.8	8.6	9.0	8.8	8.6	8.4	8.0
2.5	2.41	3.22	7.0	10.1	9.8	9.6	9.3	9.9	9.7	9.4	9.2	9.6	9.4	9.2	9.0	9.2	9.1	8.9	8.7	8.3
3	2.88	3.81	10.0	10.3	10.1	9.9	9.7	10.1	9.9	9.7	9.6	9.8	9.6	9.4	9.3	9.4	9.3	9.2	9.0	8.6

