

| 屋内照明器具特性 |                                |
|----------|--------------------------------|
| 品番 (品名)  | XND9097SW                      |
| 光源       | LED4000_80_10300 ×1 10300.0 lm |
| 管理番号     | K0179649 ( 0 ) DB 1            |
| BZ分類     | BZ1                            |

| 器具効率             |           | 100 %<br><br>上方光束<br>0 %<br>下方光束       | 反射率       | 天井   | 80 %              |     |     |      | 70 % |     |     |     | 50 % |     |     |     | 30 % |     |     |     | 0 % |    |
|------------------|-----------|----------------------------------------|-----------|------|-------------------|-----|-----|------|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|-----|----|
|                  |           |                                        |           | 壁    | 70                | 50  | 30  | 10   | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 0 % |    |
|                  |           |                                        |           | 床    | 10 %              |     |     |      | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |     |     | 0 % |    |
|                  |           |                                        |           | 室指数  | 照明率 ( X0.01 ) ZCM |     |     |      |      |     |     |     |      |     |     |     |      |     |     |     |     |    |
| 保守率              |           | 良<br>中<br>否                            | 0.76      | 0.6  | 71                | 63  | 57  | 53   | 70   | 62  | 57  | 53  | 69   | 61  | 56  | 53  | 67   | 61  | 56  | 53  | 51  |    |
|                  |           |                                        | 0.72      | 0.8  | 81                | 73  | 68  | 64   | 80   | 72  | 67  | 64  | 78   | 71  | 67  | 63  | 76   | 70  | 66  | 63  | 62  |    |
|                  |           |                                        | 0.64      | 1.0  | 86                | 80  | 75  | 71   | 85   | 79  | 74  | 71  | 83   | 78  | 74  | 70  | 81   | 77  | 73  | 70  | 68  |    |
|                  |           |                                        |           | 1.25 | 91                | 85  | 81  | 77   | 90   | 84  | 80  | 77  | 88   | 83  | 79  | 76  | 86   | 82  | 78  | 76  | 74  |    |
| 下方投影面積<br>等価発光面積 |           | cm <sup>2</sup><br><br>cm <sup>2</sup> |           | 1.5  | 94                | 89  | 85  | 81   | 93   | 88  | 84  | 81  | 91   | 86  | 83  | 80  | 89   | 85  | 82  | 80  | 78  |    |
|                  |           |                                        |           | 2.0  | 98                | 93  | 90  | 87   | 97   | 93  | 89  | 87  | 94   | 91  | 88  | 86  | 92   | 89  | 87  | 85  | 83  |    |
|                  |           |                                        |           | 2.5  | 100               | 96  | 93  | 91   | 99   | 95  | 93  | 90  | 96   | 94  | 91  | 89  | 94   | 92  | 90  | 88  | 86  |    |
|                  |           |                                        |           | 3.0  | 101               | 98  | 96  | 93   | 100  | 97  | 95  | 93  | 98   | 96  | 93  | 92  | 96   | 94  | 92  | 91  | 88  |    |
| 取付<br>高さ         | 器具間隔最大限   |                                        |           | 4.0  | 103               | 101 | 99  | 97   | 102  | 100 | 98  | 96  | 100  | 98  | 96  | 95  | 98   | 96  | 95  | 93  | 91  |    |
|                  | 横方向 ( A ) |                                        | 縦方向 ( B ) |      |                   | 5.0 | 104 | 102  | 101  | 99  | 103 | 101 | 100  | 98  | 101 | 99  | 98   | 97  | 99  | 97  | 96  | 95 |
|                  | H m       |                                        | 1.15 H m  |      | 1.15 H m          |     |     | 7.0  | 105  | 104 | 103 | 101 | 104  | 103 | 102 | 101 | 102  | 101 | 100 | 99  | 100 | 99 |
|                  |           |                                        |           |      |                   |     |     | 10.0 | 106  | 105 | 104 | 103 | 105  | 104 | 103 | 102 | 103  | 102 | 101 | 101 | 100 | 99 |

