

屋内照明器具特性

品番 (品名)	L G W 5 0 6 3 1 F	
光源	LDA7L - G / E / W × 2	810.0 lm
管理番号	K0169055 (0) DB 1	
BZ分類	BZ6	

器具効率	63%	天井	80%				70%				50%				30%				0%		
	上方光束		10%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		53%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	3.2	2.4	1.9	1.5	3.0	2.3	1.8	1.5	2.8	2.2	1.7	1.4	2.6	2.0	1.6	1.4	1.2	
	中	0.6	0.8	3.8	3.0	2.4	2.1	3.6	2.9	2.4	2.0	3.3	2.7	2.3	1.9	3.0	2.5	2.1	1.8	1.6	
	否	0.56	1.0	4.2	3.4	2.9	2.5	4.0	3.3	2.8	2.4	3.7	3.1	2.6	2.3	3.4	2.9	2.5	2.2	1.9	
	下方投影面積	c m ²		1.25	4.5	3.8	3.3	2.9	4.3	3.7	3.2	2.8	4.0	3.4	3.0	2.7	3.7	3.2	2.9	2.6	2.3
等価発光面積	c m ²		1.5	4.8	4.1	3.6	3.2	4.6	4.0	3.5	3.2	4.2	3.7	3.3	3.0	3.9	3.5	3.1	2.9	2.5	
	c m ²		2.0	5.1	4.6	4.1	3.7	4.9	4.4	4.0	3.7	4.6	4.1	3.8	3.5	4.2	3.9	3.6	3.3	3.0	
取付高さ	器具間隔最大限		2.5	5.4	4.9	4.5	4.1	5.2	4.7	4.3	4.0	4.8	4.4	4.1	3.8	4.4	4.1	3.9	3.6	3.2	
	横方向 (A)	縦方向 (B)	3.0	5.5	5.1	4.7	4.4	5.3	4.9	4.6	4.3	4.9	4.6	4.3	4.1	4.6	4.3	4.1	3.9	3.5	
H m	1.33 H m	1.33 H m	4.0	5.8	5.4	5.1	4.8	5.6	5.2	4.9	4.7	5.2	4.9	4.6	4.4	4.8	4.6	4.4	4.2	3.8	
			5.0	5.9	5.6	5.3	5.0	5.7	5.4	5.2	4.9	5.3	5.1	4.9	4.7	4.9	4.8	4.6	4.4	4.0	
			7.0	6.1	5.8	5.6	5.4	5.9	5.6	5.4	5.2	5.5	5.3	5.1	5.0	5.1	5.0	4.8	4.7	4.3	
			10.0	6.2	6.0	5.8	5.7	6.0	5.8	5.7	5.5	5.6	5.5	5.4	5.2	5.3	5.2	5.1	4.9	4.5	

