

屋内照明器具特性	
品番 (品名)	L G W 5 0 6 3 2 F
光源	LDA7N- G/ E/ W ×2 810.0 l m
管理番号	K0169056 (0) DB 1
B Z 分類	B Z 6

器具効率	53 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	8 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	45 %	室指数	照明率 (X0.01)																				Z C M
保守率	良 中 否 0.63 0.6 0.56	0.6	27	20	16	13	26	19	15	12	23	18	14	12	22	17	14	11	10				
		0.8	32	25	21	17	30	24	20	17	28	23	19	16	26	21	18	16	14				
		1.0	35	29	24	21	33	28	24	20	31	26	22	19	28	24	21	19	16				
		1.25	38	32	28	24	36	31	27	24	33	29	26	23	31	27	24	22	19				
下方投影面積	c m ²	1.5	40	35	31	27	39	34	30	27	35	31	28	25	33	29	26	24	21				
		2.0	43	38	35	31	41	37	34	31	38	35	32	29	35	32	30	28	25				
取付高さ	器具間隔最大限		2.5	45	41	38	35	43	40	36	34	40	37	34	32	37	35	32	30	27			
	横方向 (A)	縦方向 (B)	3.0	47	43	40	37	45	41	39	36	42	39	36	34	39	36	34	32	29			
H m	1.33 H m	1.33 H m	4.0	48	45	43	40	47	44	41	39	43	41	39	37	40	39	37	35	32			
			5.0	50	47	45	42	48	45	43	41	45	43	41	39	42	40	39	37	34			
			7.0	51	49	47	45	49	47	46	44	46	45	43	42	43	42	41	40	36			
			10.0	52	51	49	48	50	49	48	46	47	46	45	44	44	43	43	42	38			

