

屋内照明器具特性

品番 (品名)	LGC31610														
光源	LED6200_70_4299 x1 4299.0 lm														
管理番号	K0171644(0)DR1														
BZ分類	BZ6/0.7/BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	8%	室指数	照明率 (X0.01)																ZCM		
下方光束	92%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	53	41	33	27	52	40	32	27	48	38	31	26	45	36	30	26	23		
		0.8	63	51	43	37	61	50	42	36	57	48	41	35	54	45	39	35	32		
		1.0	70	58	50	44	67	57	49	43	63	54	47	42	59	52	46	41	38		
		1.25	75	65	57	51	73	64	56	50	69	61	54	49	65	58	52	48	44		
下方投影面積	c m ²	1.5	80	70	63	57	77	68	61	56	73	65	59	54	69	62	57	53	49		
		2.0	85	77	70	65	83	75	69	64	78	72	67	62	74	69	64	60	56		
取付高さ	器具間隔最大限		2.5	89	82	76	71	87	80	74	70	82	77	72	68	78	73	69	66	61	
	横方向 (A)	縦方向 (B)	3.0	92	85	80	75	89	83	78	74	85	80	76	72	80	76	73	70	65	
H m	1.35 H m	1.35 H m	4.0	95	90	85	81	93	88	84	80	88	84	81	77	84	81	78	75	70	
			5.0	97	93	89	85	95	91	87	84	90	87	84	81	86	83	81	78	74	
			7.0	99	96	93	90	97	94	91	89	93	90	88	86	89	87	85	83	78	
			10.0	101	99	97	94	99	97	95	93	95	93	91	90	91	89	88	86	81	

