

屋内照明器具特性	
品番 (品名)	LGC55820
光源	LED6500_70_4690 ×1 4690.0 lm
管理番号	K0182157 (0) DB 1
BZ分類	BZ5

器具効率		1 0 0 %	天井 反射率	8 0 %					7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %					1 0 %				1 0 %				1 0 %				0 %		
上方光束 下方光束		1 1 % 8 9 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
保守率		良 中 否		0 . 6	5 5	4 3	3 5	2 9	5 3	4 2	3 4	2 9	4 9	4 0	3 3	2 8	4 6	3 8	3 2	2 8	2 5			
			0 . 6	6 4	5 3	4 5	3 9	6 2	5 2	4 4	3 9	5 8	4 9	4 3	3 8	5 5	4 7	4 1	3 7	3 4				
			1 . 0	7 1	6 0	5 2	4 6	6 8	5 8	5 1	4 6	6 4	5 6	4 9	4 4	6 0	5 3	4 7	4 3	4 0				
			0 . 5 6	1 . 2 5	7 7	6 7	5 9	5 3	7 4	6 5	5 8	5 3	6 9	6 2	5 6	5 1	6 5	5 9	5 4	5 0	4 6			
下方投影面積		cm ²	1 . 5	8 1	7 2	6 5	5 9	7 8	7 0	6 3	5 8	7 3	6 6	6 1	5 6	6 9	6 3	5 8	5 4	5 0				
等価発光面積		cm ²	2 . 0	8 6	7 8	7 2	6 7	8 4	7 7	7 1	6 6	7 9	7 3	6 8	6 4	7 4	6 9	6 5	6 2	5 7				
取付 高さ	器具間隔最大限		2 . 5	9 0	8 3	7 7	7 3	8 7	8 1	7 6	7 1	8 2	7 7	7 3	6 9	7 7	7 3	7 0	6 6	6 2				
	横方向 (A)		縦方向 (B)		3 . 0	9 2	8 6	8 1	7 7	8 9	8 4	8 0	7 5	8 5	8 0	7 6	7 3	8 0	7 6	7 3	7 0	6 5		
1 . 5m	1 . 9 7 m	1 . 9 5 m	4 . 0	9 5	9 1	8 6	8 3	9 3	8 8	8 5	8 1	8 8	8 4	8 1	7 8	8 3	8 0	7 7	7 5	7 0				
2	2 . 6	2 . 5 7	5 . 0	9 7	9 3	9 0	8 6	9 5	9 1	8 8	8 5	9 0	8 7	8 4	8 1	8 5	8 3	8 0	7 8	7 3				
2 . 5	3 . 2 5	3 . 2 1	7 . 0	9 9	9 6	9 4	9 1	9 7	9 4	9 2	8 9	9 2	9 0	8 8	8 6	8 8	8 6	8 4	8 2	7 7				
3	3 . 8 7	3 . 8 3	1 0 . 0	1 0 1	9 9	9 7	9 5	9 9	9 7	9 5	9 3	9 4	9 2	9 1	8 9	8 9	8 8	8 7	8 6	8 0				

