

屋内照明器具特性	
品番 (品名)	L G C 3 5 8 2 7
光源	LED6500_70_3920 ×1 3920.0 lm
管理番号	K0182159 (0) DB 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		12 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		88 %																						
保守率		良 中 否	0.63	0.6	0.6	54	41	33	28	52	40	33	27	48	38	31	27	45	36	30	26	23		
			0.6	0.8	63	51	43	37	61	50	42	37	57	47	41	36	53	45	39	35	31			
			0.56	1.0	69	58	50	44	67	57	49	43	62	54	47	42	58	51	45	41	37			
				1.25	75	65	57	51	73	63	56	50	68	60	54	49	63	57	51	47	43			
下方投影面積		cm ²	1.5	79	70	62	57	77	68	61	56	72	64	58	54	67	61	56	52	48				
			2.0	85	77	70	65	82	75	69	64	77	71	66	61	72	67	63	59	54				
等価発光面積		cm ²	2.5	88	81	75	70	86	79	74	69	81	75	71	66	76	71	67	64	59				
			3.0	91	85	79	75	88	83	78	73	83	78	74	70	78	74	71	68	63				
1.5m		1.92 m	1.92 m	4.0	94	89	85	81	92	87	83	79	86	83	79	76	82	78	75	73	67			
2		2.53	2.53	5.0	96	92	88	85	94	90	86	83	88	85	82	80	84	81	79	76	71			
2.5		3.15	3.15	7.0	99	95	92	90	96	93	90	88	91	89	86	84	86	84	82	80	75			
3		3.78	3.78	10.0	101	98	96	94	98	96	94	92	93	91	89	88	88	87	85	84	78			

