

屋内照明器具特性	
品番 (品名)	L G C 4 5 8 2 9
光源	LED6500_70_4290 ×1 4290.0 lm
管理番号	K0182169 (0) DB 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %				
				床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
上方光束		7 %	室指数	照明率 (X 0 . 0 1)																				Z C M	
下方光束		9 3 %																							
保守率		良 中 否	0 . 6 3	0 . 6	5 5	4 3	3 5	2 9	5 3	4 2	3 4	2 9	5 0	4 0	3 3	2 9	4 7	3 9	3 3	2 8	2 6				
			0 . 6	0 . 8	6 5	5 3	4 5	3 9	6 3	5 2	4 4	3 9	5 9	5 0	4 3	3 8	5 6	4 8	4 2	3 7	3 5				
			0 . 5 6	1 . 0	7 1	6 0	5 2	4 6	6 9	5 9	5 2	4 6	6 5	5 7	5 0	4 5	6 2	5 4	4 9	4 4	4 1				
				1 . 2 5	7 7	6 7	6 0	5 4	7 5	6 6	5 9	5 3	7 1	6 3	5 7	5 2	6 7	6 1	5 5	5 1	4 8				
下方投影面積		c m ²	1 . 5	8 1	7 2	6 5	5 9	7 9	7 1	6 4	5 9	7 5	6 8	6 2	5 7	7 1	6 5	6 0	5 6	5 2					
等価発光面積		c m ²	2 . 0	8 7	7 9	7 3	6 7	8 5	7 7	7 2	6 7	8 0	7 4	6 9	6 5	7 6	7 1	6 7	6 3	6 0					
取付 高さ	器具間隔最大限		2 . 5	9 0	8 4	7 8	7 3	8 8	8 2	7 7	7 2	8 4	7 9	7 4	7 0	8 0	7 6	7 2	6 8	6 5					
	横方向 (A)	縦方向 (B)	3 . 0	9 3	8 7	8 2	7 7	9 1	8 5	8 0	7 6	8 6	8 2	7 8	7 4	8 2	7 9	7 5	7 2	6 8					
1 . 5m	1 . 9 7 m	2 . 0 3 m	4 . 0	9 6	9 1	8 7	8 3	9 4	8 9	8 5	8 2	9 0	8 6	8 3	8 0	8 6	8 3	8 0	7 7	7 3					
2	2 . 6	2 . 6 7	5 . 0	9 8	9 4	9 0	8 7	9 6	9 2	8 9	8 6	9 2	8 9	8 6	8 3	8 8	8 5	8 3	8 1	7 6					
2 . 5	3 . 2 4	3 . 3 3	7 . 0	1 0 0	9 7	9 4	9 2	9 8	9 5	9 3	9 0	9 4	9 2	9 0	8 8	9 0	8 8	8 7	8 5	8 0					
3	3 . 8 6	3 . 9 6	1 0 . 0	1 0 2	1 0 0	9 8	9 6	1 0 0	9 8	9 6	9 4	9 6	9 4	9 3	9 1	9 2	9 1	9 0	8 8	8 4					

