

屋内照明器具特性	
品番 (品名)	L G C 3 5 8 3 0
光源	LED6500_70_3970 ×1 3970.0 lm
管理番号	K0182148 (0) DB 1
B Z 分類	B Z 5

器具効率		100 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	55	43	35	30	53	42	35	29	50	40	34	29	47	39	33	28	26	
			0.6	0.8	65	53	46	40	63	52	45	39	59	50	44	39	56	48	42	38	35	
			0.56	1.0	72	61	53	47	69	59	52	47	65	57	51	46	62	55	49	45	42	
				1.25	77	68	60	55	75	66	59	54	71	63	57	53	67	61	56	51	48	
下方投影面積 等価発光面積		cm ²		1.5	82	73	66	60	79	71	65	59	75	68	62	58	71	65	60	56	53	
			cm ²	2.0	87	80	73	68	85	78	72	67	80	75	70	66	76	71	67	64	60	
取付 高さ	器具間隔最大限			2.5	91	84	79	74	88	82	77	73	84	79	75	71	80	76	72	69	65	
	横方向 (A)		縦方向 (B)	3.0	93	87	82	78	91	86	81	77	86	82	78	75	82	79	75	73	68	
1.5m	1.97 m	1.97 m	4.0	96	92	88	84	94	90	86	83	90	86	83	80	86	83	80	78	73		
2	2.59	2.59	5.0	98	94	91	88	96	92	89	86	92	89	86	84	88	85	83	81	76		
2.5	3.21	3.21	7.0	100	98	95	92	98	96	93	91	94	92	90	88	90	88	86	85	80		
3	3.83	3.83	10.0	102	100	98	96	100	98	96	94	96	94	93	91	92	91	89	88	83		

