

| 屋内照明器具特性 |                              |
|----------|------------------------------|
| 品番 (品名)  | L G C 3 5 1 2 4              |
| 光源       | LED6500_70_3980 ×1 3980.0 lm |
| 管理番号     | K0183969 ( 0 ) DB 1          |
| B Z 分類   | B Z 5                        |

| 器具効率         |                     | 100 %           | 反射率  | 天井                  | 80 % |    |    |     | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |
|--------------|---------------------|-----------------|------|---------------------|------|----|----|-----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|
|              |                     |                 |      | 壁                   | 70   | 50 | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |
|              |                     |                 |      | 床                   | 10 % |    |    |     | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |
| 上方光束<br>下方光束 |                     | 6 %<br>94 %     | 室指数  | 照明率 ( X0.01 ) Z C M |      |    |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |  |
| 保守率          |                     | 良<br>中<br>否     | 0.63 | 0.6                 | 56   | 44 | 37 | 31  | 55   | 43 | 36 | 31 | 52   | 42 | 35 | 31 | 49   | 40 | 34 | 30 | 28  |  |
|              |                     |                 | 0.6  | 0.8                 | 66   | 55 | 47 | 41  | 64   | 54 | 47 | 41 | 61   | 52 | 45 | 40 | 58   | 50 | 44 | 40 | 37  |  |
|              |                     |                 | 0.56 | 1.0                 | 73   | 62 | 55 | 49  | 71   | 61 | 54 | 48 | 67   | 59 | 52 | 48 | 64   | 57 | 51 | 47 | 44  |  |
|              |                     |                 |      | 1.25                | 79   | 69 | 62 | 56  | 76   | 68 | 61 | 56 | 73   | 65 | 59 | 55 | 69   | 63 | 58 | 53 | 50  |  |
| 下方投影面積       |                     | cm <sup>2</sup> | 1.5  | 83                  | 74   | 67 | 62 | 80  | 72   | 66 | 61 | 76 | 70   | 64 | 60 | 73 | 67   | 62 | 59 | 55 |     |  |
| 等価発光面積       |                     | cm <sup>2</sup> | 2.0  | 88                  | 81   | 75 | 70 | 86  | 79   | 74 | 69 | 82 | 76   | 71 | 67 | 78 | 73   | 69 | 66 | 62 |     |  |
| 取付<br>高さ     | 器具間隔最大限             |                 | 2.5  | 92                  | 85   | 80 | 75 | 89  | 84   | 79 | 75 | 85 | 80   | 76 | 73 | 82 | 78   | 74 | 71 | 67 |     |  |
|              | 横方向 ( A ) 縦方向 ( B ) |                 | 3.0  | 94                  | 88   | 84 | 80 | 92  | 87   | 82 | 79 | 88 | 84   | 80 | 77 | 84 | 80   | 77 | 75 | 71 |     |  |
| 1.5m         | 1.93 m              | 1.93 m          | 4.0  | 97                  | 93   | 89 | 85 | 95  | 91   | 87 | 84 | 91 | 88   | 84 | 82 | 87 | 84   | 82 | 79 | 75 |     |  |
| 2            | 2.53                | 2.53            | 5.0  | 99                  | 95   | 92 | 89 | 97  | 93   | 90 | 88 | 93 | 90   | 87 | 85 | 89 | 87   | 85 | 83 | 78 |     |  |
| 2.5          | 3.14                | 3.14            | 7.0  | 101                 | 98   | 96 | 93 | 99  | 96   | 94 | 92 | 95 | 93   | 91 | 89 | 91 | 90   | 88 | 87 | 82 |     |  |
| 3            | 3.76                | 3.77            | 10.0 | 103                 | 101  | 99 | 97 | 101 | 99   | 97 | 95 | 97 | 95   | 94 | 92 | 93 | 92   | 91 | 90 | 85 |     |  |

