

屋内照明器具特性	
品番 (品名)	XAS30834
光源	LLD40404CQ1 (KAKUSAN) ×1 860.0 lm
管理番号	K0184330 (0) DR1
BZ分類	BZ3/0.7/BZ2

器具効率		50 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
上方光束		0 %	室指数	照明率 (X0.01)																				Z C M	
下方光束		50 %																							
保守率		良 中 否	0.67	0.6	33	28	25	23	32	28	25	23	31	27	24	22	31	27	24	22	22				
			0.63	0.8	38	33	30	28	37	33	30	28	36	33	30	28	35	32	30	28	27				
			0.56	1.0	41	37	34	32	40	37	34	32	39	36	34	32	38	35	33	32	31				
				1.25	44	40	38	36	43	40	37	35	42	39	37	35	41	38	36	35	34				
下方投影面積		cm ²	1.5	45	42	40	38	45	42	40	38	44	41	39	37	42	40	39	37	36					
等価発光面積			cm ²	2.0	48	45	43	41	47	45	43	41	46	44	42	41	45	43	42	40	39				
2.5	49			47	45	44	48	46	45	43	47	45	44	43	46	45	43	42	41						
取付 高さ	器具間隔最大限			2.5	49	47	45	44	48	46	45	43	47	45	44	43	46	45	43	42	41				
	横方向 (A)		縦方向 (B)		3.0	50	48	46	45	49	47	46	45	48	47	45	44	47	46	45	44	43			
H m	1.16 H m		1.16 H m		4.0	51	49	48	47	50	49	48	47	49	48	47	46	48	47	46	45	44			
					5.0	51	50	49	48	51	50	49	48	50	49	48	47	49	48	47	47	45			
					7.0	52	51	51	50	52	51	50	49	50	50	49	49	49	49	48	48	46			
					10.0	53	52	52	51	52	52	51	51	51	51	50	50	50	49	49	49	47			

