

屋内照明器具特性	
品番 (品名)	XAS35832
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 l m
管理番号	K0184331 (0) DR 1
BZ分類	BZ1

器具効率		85 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		0 %	室指数	照明率 (X0.01)																				Z	C	M
下方光束		85 %																								
保守率		良	0.67	0.6	67	61	57	54	66	61	57	54	65	60	57	54	64	59	56	54	53					
		中	0.63	0.8	74	68	64	62	73	68	64	62	71	67	64	61	70	66	63	61	60					
		否	0.56	1.0	77	73	69	66	77	72	69	66	75	71	68	66	74	70	68	66	64					
				1.25	81	76	73	71	80	76	73	70	78	75	72	70	77	74	71	70	68					
下方投影面積		c m ²		1.5	83	79	76	74	82	78	76	73	80	77	75	73	78	76	74	72	71					
等価発光面積		c m ²		2.0	85	82	80	78	84	81	79	77	82	80	78	77	81	79	77	76	74					
取付 高さ	器具間隔最大限			2.5	87	84	82	80	86	83	81	80	84	82	80	79	82	81	79	78	76					
	横方向 (A)		縦方向 (B)	3.0	88	86	84	82	87	85	83	82	85	83	82	81	83	82	81	80	78					
H m	0.74 H m		0.74 H m	4.0	89	87	86	84	88	86	85	84	86	85	84	83	84	83	82	82	80					
				5.0	90	88	87	86	89	87	86	85	87	86	85	84	85	84	83	83	81					
				7.0	91	89	89	88	90	89	88	87	88	87	86	85	86	85	85	84	82					
				10.0	91	90	90	89	90	89	89	88	88	88	87	87	86	86	86	85	83					

