

屋内照明器具特性	
品番 (品名)	LGC51128K
光源	LED6200_70_5100 ×1 5100.0 lm
管理番号	K0184376 (0) D 1
BZ分類	BZ5

器具効率		100 % 上方光束 10 % 下方光束 90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) ZCM															
保守率		良 中 否	0.63	0.6	54	42	34	28	52	41	33	28	49	39	32	27	46	37	31	26	24	
			0.6	0.8	64	52	44	38	61	51	43	37	57	48	41	36	54	46	40	35	32	
			0.56	1.0	70	59	51	45	68	58	50	44	63	55	48	43	59	52	46	42	39	
				1.25	76	66	58	52	73	64	57	51	69	61	55	50	65	58	53	48	45	
下方投影面積 等価発光面積		cm ² cm ²	1.5	80	71	63	58	78	69	62	57	73	66	60	55	68	62	57	53	49		
			2.0	86	78	71	66	83	76	70	65	78	72	67	63	74	69	64	61	56		
取付 高さ	器具間隔最大限		2.5	89	82	77	72	87	80	75	70	82	76	72	68	77	73	69	66	61		
	横方向 (A)	縦方向 (B)	3.0	92	86	80	76	89	84	79	75	84	80	76	72	80	76	72	69	65		
H m	1.28 H m	1.28 H m	4.0	95	90	86	82	92	88	84	80	88	84	80	77	83	80	77	75	70		
			5.0	97	93	89	86	94	91	87	84	90	86	84	81	85	82	80	78	73		
			7.0	99	96	93	91	97	94	91	89	92	90	87	85	88	86	84	82	77		
			10.0	101	99	97	95	99	97	95	93	94	92	91	89	90	88	87	85	80		

