

屋内照明器具特性

品番 (品名)	L S E B 3 2 4 5									
光源	LDA4L - H - E17 / E / S / W / 2 ×1					440.0 l m				
管理番号	K0170957 (0) DR 1									
B Z 分類	BZ6 / 0.7 / BZ5 / 1.1 / BZ6									

器具効率	98 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		26 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		72 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.67	0.6	50	39	31	26	48	37	30	25	43	34	28	23	39	31	26	22	18	
	中	0.63	0.8	59	48	40	34	56	46	39	33	50	42	36	31	45	38	33	29	25	
	否	0.56	1.0	65	54	46	41	62	52	45	39	55	47	41	37	50	43	38	34	29	
	下方投影面積	c m ²		1.25	71	60	53	47	67	58	51	45	60	53	47	42	54	48	43	39	33
等価発光面積	c m ²		1.5	74	65	58	52	71	62	55	50	63	57	51	47	57	51	47	43	37	
	c m ²		2.0	80	71	65	59	76	68	62	57	68	62	57	53	61	57	53	49	42	
取付高さ	器具間隔最大限		2.5	83	76	70	65	79	72	67	62	71	66	62	58	64	60	56	53	46	
	横方向 (A)	縦方向 (B)	3.0	85	79	73	69	81	76	71	66	74	69	65	61	66	63	59	56	48	
H m	1.34 H m	1.34 H m	4.0	88	83	79	74	84	80	75	72	77	73	69	66	69	66	63	61	52	
			5.0	90	86	82	78	86	82	79	75	79	75	72	69	71	69	66	64	55	
			7.0	93	89	86	83	89	86	83	80	81	78	76	74	74	72	70	68	59	
			10.0	95	92	90	87	91	88	86	84	83	81	79	77	76	74	73	71	62	

