

屋内照明器具特性	
品番 (品名)	L G C 3 1 1 6 0 K
光源	LED6200_70_4299 ×1 4299.0 lm
管理番号	K0183675 (0) D 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01)															
保守率		良 中 否	0.63	0.6	54	42	34	29	52	41	34	29	49	39	33	28	46	37	31	27	24	
			0.6	0.8	64	52	44	39	62	51	44	38	58	48	42	37	54	46	40	36	33	
			0.56	1.0	70	59	52	46	68	58	51	45	64	55	49	44	59	52	47	42	39	
				1.25	76	66	59	53	74	64	57	52	69	61	55	50	65	58	53	49	45	
下方投影面積		c m ²	1.5	80	71	64	58	78	69	63	57	73	66	60	55	68	62	58	54	49		
等価発光面積				c m ²	2.0	86	78	72	66	83	76	70	65	78	72	67	63	73	69	64	61	
取付高さ	器具間隔最大限				2.5	89	83	77	72	87	80	75	71	82	76	72	68	77	73	69	66	
	横方向 (A)				縦方向 (B)		3.0	92	86	81	76	89	84	79	75	84	80	76	72	79	76	
H m	1.25 H m	1.25 H m	4.0		95	90	86	82	92	88	84	81	87	84	80	77	83	80	77	74		
			5.0	97	93	89	86	94	91	87	84	89	86	83	81	85	82	80	78			
			7.0	99	96	93	91	97	94	91	89	92	89	87	85	87	85	83	82			
			10.0	101	99	97	95	99	96	94	93	94	92	90	89	89	88	86	85			

