

屋内照明器具特性	
品番 (品名)	L G C 3 1 1 6 2 K
光源	LED6200_70_4299 ×1 4299.0 lm
管理番号	K0183808 (0) D 1
B Z 分類	B Z 5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		8 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		92 %																						
保守率		良 中 否	0.63	0.6	55	42	35	29	53	42	34	29	50	40	33	28	47	38	32	28	25			
			0.6	0.8	64	53	45	39	62	52	44	38	59	49	43	38	55	47	41	37	34			
			0.56	1.0	71	60	52	46	69	59	51	46	65	56	50	44	61	54	48	43	40			
				1.25	77	67	59	53	74	65	58	53	70	62	56	51	66	60	54	50	47			
下方投影面積		cm ²	1.5	81	72	64	59	78	70	63	58	74	67	61	56	70	64	59	55	51				
等価発光面積		cm ²	2.0	86	79	72	67	84	77	71	66	80	74	68	64	75	70	66	62	58				
取付 高さ	器具間隔最大限		2.5	90	83	78	73	88	81	76	72	83	78	73	69	79	75	71	67	63				
	横方向 (A)	縦方向 (B)	3.0	92	87	81	77	90	85	80	76	86	81	77	73	81	78	74	71	67				
H m	1.26 H m	1.26 H m	4.0	96	91	87	83	93	89	85	81	89	85	82	79	85	82	79	76	72				
			5.0	98	94	90	87	95	92	88	85	91	88	85	82	87	84	82	80	75				
			7.0	100	97	94	91	98	95	92	90	93	91	89	87	89	87	85	84	79				
			10.0	102	100	97	95	100	97	96	94	95	94	92	90	91	90	88	87	82				

