

屋内照明器具特性	
品番 (品名)	LGC51148K
光源	LED6200_70_5100 ×1 5100.0 lm
管理番号	K0168768 (0) DB 1
BZ分類	BZ5

器具効率		100 % 上方光束 6 % 下方光束 94 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	55	43	35	30	54	42	35	29	51	41	34	29	48	39	33	29	26	
			0.6	0.8	65	53	45	40	63	52	45	39	60	50	44	39	57	49	43	38	35	
			0.56	1.0	72	61	53	47	70	59	52	47	66	57	51	46	62	55	49	45	42	
				1.25	77	68	60	54	75	66	59	54	71	64	58	53	68	61	56	52	48	
下方投影面積		cm ²		1.5	82	72	65	60	79	71	64	59	75	68	63	58	72	66	61	57	53	
			等価発光面積	cm ²	2.0	87	79	73	68	85	78	72	67	81	75	70	66	77	72	68	64	60
取付 高さ	器具間隔最大限			2.5	91	84	78	74	88	82	77	73	84	79	75	71	80	76	72	69	65	
	横方向 (A)		縦方向 (B)	3.0	93	87	82	78	91	86	81	77	87	82	78	75	83	79	76	73	69	
H m	1.26 H m		1.26 H m	4.0	96	92	87	84	94	90	86	82	90	86	83	80	86	83	81	78	74	
				5.0	98	94	91	87	96	93	89	86	92	89	86	84	88	86	84	81	77	
				7.0	101	98	95	92	98	96	93	91	95	92	90	88	91	89	87	85	81	
				10.0	102	100	98	96	100	98	96	95	96	95	93	92	93	91	90	89	84	

