

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 8 7
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0185493 (0) DR 1
BZ分類	BZ4 / 0.7 / BZ3

器具効率		90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数		照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	55	45	38	34	54	44	38	34	52	43	38	33	50	42	37	33	32	
			0.63	0.8	65	56	49	45	64	55	49	45	61	54	49	44	59	53	48	44	43	
			0.56	1.0	71	63	57	53	70	62	57	53	68	61	56	52	66	60	56	52	50	
				1.25	77	70	64	60	75	69	64	60	73	67	63	59	71	66	62	59	57	
下方投影面積		cm ²		1.5	80	74	69	65	79	73	68	65	77	71	67	64	74	70	66	63	62	
等価発光面積			cm ²	2.0	85	79	75	72	83	79	75	71	81	77	74	71	79	75	72	70	68	
取付高さ	器具間隔最大限			2.5	87	83	79	76	86	82	79	76	84	80	77	75	82	79	76	74	72	
	横方向 (A)			縦方向 (B)		3.0	89	85	82	79	88	84	81	79	86	83	80	78	83	81	79	77
H m	1.27 H m	1.27 H m		4.0	91	88	86	84	90	87	85	83	88	86	84	82	86	84	82	81	78	
			5.0	93	90	88	86	91	89	87	85	89	87	86	84	87	86	84	83	81		
			7.0	94	92	91	89	93	91	90	88	91	89	88	87	89	88	87	86	83		
			10.0	95	94	93	92	94	93	92	91	92	91	90	89	90	89	88	88	85		

