

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 8 7
光源	LLD40404CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0185502 (0) DR 1
B Z 分類	BZ3 / 1.1 / BZ2

器具効率		92 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	58	48	42	37	57	48	41	37	55	47	41	37	53	46	41	37	35
			0.63	0.8	68	60	54	49	67	59	53	49	65	58	53	49	63	57	52	49	47
			0.56	1.0	75	67	62	57	74	66	61	57	71	65	60	57	69	64	60	57	55
				1.25	80	73	68	64	79	73	68	64	77	71	67	64	75	70	66	63	62
下方投影面積 等価発光面積		c m ²		1.5	83	77	73	69	82	77	72	69	80	75	71	68	78	74	71	68	66
				2.0	88	83	79	76	86	82	78	75	84	80	77	75	82	79	76	74	72
				2.5	90	86	83	80	89	85	82	79	87	84	81	79	85	82	80	78	76
				3.0	92	88	85	83	91	87	85	82	88	86	83	81	86	84	82	80	78
H m	1.22 H m	1.22 H m		4.0	94	91	89	87	93	90	88	86	90	88	87	85	88	87	85	84	81
				5.0	95	93	91	89	94	92	90	88	92	90	89	87	90	88	87	86	83
				7.0	96	95	93	92	95	94	92	91	93	92	91	90	91	90	89	88	86
				10.0	97	96	95	94	96	95	94	93	94	93	92	92	92	91	91	90	88

