

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 8 9
光源	LLD40001CQ1 ×1 845.0 l m
管理番号	K0185499 (1) DR 1
B Z 分類	BZ4 / 0.7 / BZ3

器具効率		77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	47	38	33	29	46	38	32	29	44	37	32	29	43	36	32	29	27
			0.63	0.8	55	48	42	39	54	47	42	38	53	46	42	38	51	45	41	38	37
			0.56	1.0	61	54	49	45	60	53	49	45	58	52	48	45	56	51	48	45	43
			1.25	66	59	55	51	64	59	55	51	62	58	54	51	61	56	53	51	49	
下方投影面積		cm ²	1.5	68	63	59	56	67	62	58	55	65	61	58	55	63	60	57	54	53	
等価発光面積			2.0	72	68	64	61	71	67	64	61	69	66	63	60	67	64	62	60	58	
取付	器具間隔最大限			2.5	74	71	68	65	73	70	67	65	71	69	66	64	70	67	65	63	62
高さ	横方向 (A)		縦方向 (B)	3.0	76	73	70	68	75	72	70	67	73	71	68	67	71	69	67	66	64
H m	1.30 H m		1.30 H m	4.0	78	75	73	71	77	75	73	71	75	73	71	70	73	72	70	69	67
				5.0	79	77	75	74	78	76	74	73	76	75	73	72	74	73	72	71	69
				7.0	80	79	77	76	79	78	77	75	77	76	75	74	76	75	74	73	71
				10.0	81	80	79	78	80	79	78	77	78	78	77	76	77	76	75	75	73

