

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 8 9
光源	LLD20001CQ1 ×1 531.0 lm
管理番号	K0185500 (0) DR 1
B Z 分類	BZ4 / 0.7 / BZ3

器具効率		87 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		87 %		室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	53	43	37	32	52	42	37	32	50	42	36	32	48	41	36	32	30
			0.63	0.8	62	54	48	43	61	53	47	43	59	52	47	43	57	51	46	43	41
			0.56	1.0	69	61	55	51	67	60	55	51	65	59	54	50	63	58	53	50	48
				1.25	74	67	62	58	72	66	61	58	70	65	61	57	68	63	60	57	55
下方投影面積		cm ²	1.5	77	71	66	62	76	70	66	62	73	69	65	62	71	67	64	61	59	
等価発光面積		cm ²	2.0	81	76	72	69	80	75	72	69	78	74	71	68	76	72	70	67	65	
取付 高さ	器具間隔最大限		2.5	84	80	76	73	83	79	76	73	80	77	74	72	78	76	73	71	69	
	横方向 (A) 縦方向 (B)		3.0	85	82	79	76	84	81	78	76	82	79	77	75	80	78	76	74	72	
H m	1.28 H m	1.28 H m	4.0	88	85	82	80	86	84	82	80	84	82	80	78	82	80	79	77	75	
			5.0	89	87	85	83	88	86	84	82	86	84	82	81	84	82	81	79	77	
			7.0	90	89	87	86	89	88	86	85	87	86	85	83	85	84	83	82	80	
			10.0	91	90	89	88	90	89	88	87	88	87	86	86	86	85	85	84	82	

