

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 8 9
光源	L L D 4 0 4 0 2 C Q 1 (S H U K O U) × 1 6 2 0 . 0 l m
管理番号	K 0 1 8 5 5 0 1 (0) D R 1
B Z 分類	B Z 1

器具効率		6 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		6 6 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6	5 1	4 6	4 3	4 1	5 1	4 6	4 3	4 1	5 0	4 6	4 3	4 1	4 9	4 5	4 3	4 1	4 0		
			0 . 8	5 6	5 2	4 9	4 7	5 6	5 2	4 9	4 7	5 5	5 1	4 9	4 7	5 4	5 1	4 8	4 7	4 6		
			1 . 0	6 0	5 6	5 3	5 1	5 9	5 5	5 3	5 1	5 8	5 5	5 2	5 1	5 7	5 4	5 2	5 0	4 9		
			1 . 2 5	6 2	5 9	5 6	5 4	6 1	5 8	5 6	5 4	6 0	5 8	5 5	5 4	5 9	5 7	5 5	5 3	5 2		
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	6 4	6 1	5 9	5 7	6 3	6 0	5 8	5 6	6 2	5 9	5 8	5 6	6 1	5 9	5 7	5 6	5 5		
			2 . 0	6 6	6 3	6 1	6 0	6 5	6 3	6 1	6 0	6 4	6 2	6 0	5 9	6 2	6 1	6 0	5 8	5 7		
取付 高さ	器具間隔最大限		2 . 5	6 7	6 5	6 3	6 2	6 6	6 4	6 3	6 2	6 5	6 3	6 2	6 1	6 4	6 2	6 1	6 0	5 9		
	横方向 (A) 縦方向 (B)		3 . 0	6 8	6 6	6 5	6 3	6 7	6 6	6 4	6 3	6 6	6 4	6 3	6 2	6 4	6 3	6 2	6 1	6 0		
H m	0 . 7 4 H m	0 . 7 4 H m	4 . 0	6 9	6 7	6 6	6 5	6 8	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 5	6 4	6 4	6 3	6 1		
			5 . 0	6 9	6 8	6 7	6 6	6 9	6 8	6 7	6 6	6 7	6 6	6 6	6 5	6 6	6 5	6 5	6 4	6 2		
			7 . 0	7 0	6 9	6 9	6 8	6 9	6 9	6 8	6 7	6 8	6 7	6 7	6 6	6 6	6 6	6 5	6 5	6 3		
			1 0 . 0	7 1	7 0	6 9	6 9	7 0	6 9	6 9	6 8	6 8	6 8	6 7	6 7	6 7	6 7	6 6	6 6	6 4		

