

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 8 9
光源	L L D 3 0 2 0 C U 1 × 1 6 1 5 . 0 l m
管理番号	K 0 1 8 5 5 0 3 (0) D R 1
B Z 分類	B Z 1

器具効率			7 6 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束			7 6 %	室指数	照明率 (X 0 . 0 1) Z C M																			
下方光束																								
保守率			良 中 否	0 . 6	6 4	5 9	5 6	5 4	6 3	5 9	5 6	5 4	6 2	5 8	5 6	5 4	6 1	5 8	5 6	5 4	5 3			
				0 . 8	6 8	6 4	6 1	5 9	6 8	6 4	6 1	5 9	6 7	6 3	6 1	5 9	6 6	6 3	6 1	5 9	5 8			
				1 . 0	7 1	6 8	6 5	6 3	7 1	6 7	6 5	6 3	6 9	6 6	6 4	6 2	6 8	6 6	6 4	6 2	6 1			
				0 . 5 6	1 . 2 5	7 4	7 0	6 8	6 6	7 3	7 0	6 8	6 6	7 2	6 9	6 7	6 5	7 0	6 8	6 6	6 5	6 4		
下方投影面積			c m ²	1 . 5	7 5	7 2	7 0	6 8	7 4	7 2	7 0	6 8	7 3	7 1	6 9	6 7	7 2	7 0	6 8	6 7	6 6			
				等価発光面積			c m ²	2 . 0	7 7	7 5	7 3	7 1	7 6	7 4	7 2	7 1	7 5	7 3	7 1	7 0	7 3	7 2	7 1	7 0
取付 高さ	器具間隔最大限			2 . 5	7 8	7 6	7 5	7 3	7 7	7 6	7 4	7 3	7 6	7 4	7 3	7 2	7 4	7 3	7 2	7 1	7 0			
	横方向 (A)		縦方向 (B)	3 . 0	7 9	7 7	7 6	7 4	7 8	7 7	7 5	7 4	7 7	7 5	7 4	7 3	7 5	7 4	7 3	7 2	7 1			
H m	0 . 3 5 H m		0 . 3 5 H m	4 . 0	8 0	7 9	7 7	7 6	7 9	7 8	7 7	7 6	7 7	7 6	7 5	7 6	7 5	7 4	7 4	7 2				
				5 . 0	8 0	7 9	7 8	7 7	8 0	7 9	7 8	7 7	7 8	7 7	7 6	7 6	7 6	7 6	7 5	7 5	7 3			
				7 . 0	8 1	8 0	8 0	7 9	8 0	7 9	7 9	7 8	7 9	7 8	7 7	7 7	7 7	7 7	7 6	7 6	7 4			
				1 0 . 0	8 2	8 1	8 0	8 0	8 1	8 0	8 0	7 9	7 9	7 9	7 8	7 8	7 7	7 7	7 7	7 6	7 4			

