

屋内照明器具特性	
品番 (品名)	XLX455PHWP
光源	LED4000_85_4460 x1 4460.0 lm
管理番号	K0144272(0)DB1
BZ分類	BZ4

器具効率	100%	天井	80%				70%				50%				30%				0%		
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	0%	床	10%				10%				10%				10%				0%		
下方光束	100%	室指数	照明率 (X0.01)																ZCM		
保守率	良 中 否	0.81	0.6	5.9	4.7	3.9	3.4	5.7	4.6	3.9	3.4	5.5	4.5	3.9	3.4	5.3	4.4	3.8	3.4	3.2	
		0.77	0.8	6.9	5.8	5.0	4.5	6.8	5.7	5.0	4.5	6.5	5.6	4.9	4.5	6.2	5.5	4.9	4.4	4.2	
		0.68	1.0	7.6	6.5	5.8	5.3	7.4	6.5	5.8	5.3	7.1	6.3	5.7	5.2	6.9	6.2	5.6	5.2	5.0	
			1.25	8.1	7.2	6.6	6.0	8.0	7.2	6.5	6.0	7.7	7.0	6.4	6.0	7.4	6.8	6.3	5.9	5.7	
下方投影面積		cm ²		1.5	8.6	7.7	7.1	6.6	8.4	7.6	7.0	6.6	8.1	7.5	6.9	6.5	7.8	7.3	6.8	6.4	6.2
等価発光面積		cm ²		2.0	9.1	8.4	7.9	7.4	8.9	8.3	7.8	7.4	8.6	8.1	7.7	7.3	8.4	7.9	7.5	7.2	7.0
取付高さ	器具間隔最大限		2.5	9.4	8.9	8.4	8.0	9.3	8.7	8.3	7.9	9.0	8.5	8.1	7.8	8.7	8.3	8.0	7.7	7.5	
	横方向 (A)	縦方向 (B)	3.0	9.7	9.2	8.7	8.4	9.5	9.0	8.6	8.3	9.2	8.8	8.5	8.2	9.0	8.6	8.3	8.1	7.8	
1.5m	1.94m	2.13m	4.0	9.9	9.6	9.2	8.9	9.8	9.4	9.1	8.8	9.5	9.2	9.0	8.7	9.3	9.0	8.8	8.6	8.3	
2	2.57	2.68	5.0	10.1	9.8	9.5	9.2	10.0	9.7	9.4	9.2	9.7	9.5	9.2	9.0	9.5	9.3	9.1	8.9	8.6	
2.5	3.19	3.26	7.0	10.3	10.1	9.9	9.7	10.2	10.0	9.8	9.6	9.9	9.7	9.6	9.4	9.7	9.5	9.4	9.3	9.0	
3	3.82	3.85	10.0	10.5	10.3	10.1	10.0	10.3	10.2	10.0	9.9	10.1	10.0	9.8	9.7	9.9	9.7	9.6	9.5	9.3	

