

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 9 3
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0185528 (0) DR 1
B Z 分類	BZ3 / 1.1 / BZ2

器具効率		77 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z C M																				
保守率		良 中 否	0.67	0.6	49	40	35	31	48	40	35	31	46	39	34	31	45	38	34	31	30				
			0.63	0.8	57	50	45	41	56	49	45	41	55	49	44	41	53	48	44	41	39				
			1.0	1.0	63	56	52	48	62	56	51	48	60	55	51	48	58	54	50	47	46				
			0.56	1.25	67	62	57	54	66	61	57	54	64	60	56	54	63	59	56	53	52				
下方投影面積		cm ²	1.5	70	65	61	58	69	64	61	58	67	63	60	57	65	62	59	57	55					
			2.0	74	70	66	64	73	69	66	63	71	68	65	63	69	66	64	62	60					
等価発光面積		cm ²	2.5	76	72	70	67	75	72	69	67	73	70	68	66	71	69	67	65	64					
			3.0	77	74	72	70	76	73	71	69	74	72	70	68	72	71	69	67	66					
H m	1.22 H m	1.22 H m	4.0	79	77	75	73	78	76	74	72	76	74	73	71	74	73	71	70	68					
			5.0	80	78	76	75	79	77	76	74	77	76	74	73	75	74	73	72	70					
			7.0	81	80	78	77	80	79	78	77	78	77	76	75	76	76	75	74	72					
			10.0	82	81	80	79	81	80	79	78	79	78	78	77	77	77	76	76	74					

