

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 9 3
光源	L L D 4 0 4 0 2 C Q 1 (S H U K O U) × 1 6 2 0 . 0 l m
管理番号	K 0 1 8 5 5 2 7 (0) D R 1
B Z 分類	B Z 1

器具効率		6 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		6 0 %																						
保守率		良 中 否	0 . 6 7	0 . 6	4 7	4 2	3 9	3 7	4 6	4 2	3 9	3 7	4 5	4 2	3 9	3 7	4 4	4 1	3 9	3 7	3 6			
			0 . 6 3	0 . 8	5 1	4 8	4 5	4 3	5 1	4 7	4 5	4 3	5 0	4 7	4 4	4 3	4 9	4 6	4 4	4 2	4 2			
			0 . 5 6	1 . 0	5 4	5 1	4 8	4 6	5 4	5 0	4 8	4 6	5 3	5 0	4 8	4 6	5 2	4 9	4 7	4 6	4 5			
				1 . 2 5	5 7	5 4	5 1	4 9	5 6	5 3	5 1	4 9	5 5	5 2	5 1	4 9	5 4	5 2	5 0	4 9	4 8			
下方投影面積		c m ²	1 . 5	5 8	5 5	5 3	5 2	5 8	5 5	5 3	5 1	5 6	5 4	5 2	5 1	5 5	5 3	5 2	5 1	5 0				
等価発光面積		c m ²	2 . 0	6 0	5 8	5 6	5 5	5 9	5 7	5 6	5 4	5 8	5 6	5 5	5 4	5 7	5 6	5 4	5 3	5 2				
取付 高さ	器具間隔最大限		2 . 5	6 1	5 9	5 8	5 6	6 0	5 9	5 7	5 6	5 9	5 8	5 7	5 6	5 8	5 7	5 6	5 5	5 4				
	横方向 (A) 縦方向 (B)		3 . 0	6 2	6 0	5 9	5 8	6 1	6 0	5 8	5 7	6 0	5 9	5 8	5 7	5 9	5 8	5 7	5 6	5 5				
H m	0 . 7 4 H m	0 . 7 4 H m	4 . 0	6 3	6 2	6 0	5 9	6 2	6 1	6 0	5 9	6 1	6 0	5 9	5 8	6 0	5 9	5 8	5 7	5 6				
			5 . 0	6 3	6 2	6 1	6 1	6 3	6 2	6 1	6 0	6 1	6 1	6 0	5 9	6 0	5 9	5 9	5 8	5 7				
			7 . 0	6 4	6 3	6 2	6 2	6 3	6 3	6 2	6 1	6 2	6 1	6 1	6 0	6 1	6 0	6 0	5 9	5 8				
			1 0 . 0	6 4	6 4	6 3	6 3	6 4	6 3	6 3	6 2	6 2	6 2	6 2	6 1	6 1	6 1	6 0	6 0	5 8				

