

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 9 3
光源	LLD3000CU1 ×1 795.0 lm
管理番号	K0185529 (0) DR 1
B Z 分類	BZ4 / 0.7 / BZ3 / 2.8 / BZ2 / 4.5 / BZ3 / 6.0 / BZ2

器具効率		72 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	44	36	31	28	43	36	31	28	42	35	31	28	40	35	31	28	26
			0.63	0.8	52	45	40	37	51	45	40	37	50	44	40	37	48	43	39	36	35
			0.56	1.0	57	51	47	43	56	51	46	43	55	50	46	43	53	49	45	43	41
				1.25	62	56	52	49	61	56	52	49	59	55	51	48	57	54	51	48	47
下方投影面積		cm ²		1.5	64	60	56	53	63	59	55	53	62	58	55	52	60	57	54	52	50
			等価発光面積	cm ²	2.0	68	64	61	58	67	63	60	58	65	62	59	57	63	61	59	57
取付 高さ	器具間隔最大限			2.5	70	67	64	62	69	66	63	61	67	65	62	60	65	63	61	60	58
	横方向 (A) 縦方向 (B)			3.0	71	68	66	64	70	68	65	64	68	66	64	63	67	65	63	62	60
H m	1.22 H m	1.22 H m		4.0	73	71	69	67	72	70	68	67	70	68	67	66	68	67	66	65	63
				5.0	74	72	70	69	73	71	70	68	71	70	69	67	70	68	67	66	65
				7.0	75	74	72	71	74	73	72	71	72	71	70	70	71	70	69	68	66
				10.0	76	75	74	73	75	74	73	72	73	72	72	71	72	71	70	70	68

