

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 9 3
光源	L L D 5 0 0 0 L C C 1 × 1 1 1 4 0 . 0 l m
管理番号	K 0 1 9 0 4 2 2 (0) D R 1
B Z 分類	B Z 3 / 0 . 7 / B Z 2

器具効率		93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 7	0 . 6	61	51	45	41	60	51	45	41	58	50	44	41	56	49	44	40	39
			0 . 6 3	0 . 8	70	62	56	52	69	61	56	52	67	60	55	52	65	59	55	51	50
			0 . 5 6	1 . 0	77	69	64	60	75	68	63	59	73	67	63	59	71	66	62	59	57
				1 . 2 5	82	75	70	66	80	74	70	66	78	73	69	66	76	72	68	65	64
下方投影面積		c m ²	1 . 5	85	79	75	71	84	78	74	71	81	77	73	70	79	75	72	70	68	
			等価発光面積	c m ²	2 . 0	89	84	81	77	88	84	80	77	86	82	79	76	83	80	78	76
取付 高さ	器具間隔最大限		2 . 5	91	88	84	82	90	87	84	81	88	85	82	80	86	83	81	79	77	
	横方向 (A) 縦方向 (B)		3 . 0	93	90	87	84	92	89	86	84	90	87	85	83	88	85	84	82	80	
H m	1 . 2 6 H m	1 . 2 6 H m	4 . 0	95	93	90	88	94	92	89	88	92	90	88	86	90	88	86	85	83	
			5 . 0	96	94	92	91	95	93	91	90	93	91	90	88	91	89	88	87	85	
			7 . 0	98	96	95	93	96	95	94	92	94	93	92	91	92	91	90	89	87	
			1 0 . 0	99	97	96	95	97	96	95	95	95	94	94	93	93	93	92	91	89	

