

屋内照明器具特性	
品番 (品名)	L G B 1 5 4 8 7
光源	L L D 4 0 0 0 M L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 8 5 4 9 4 (0) D R 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3

器具効率		7 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		7 2 %																					
保守率		良 中 否	0 . 6 7	0 . 6	4 4	3 6	3 1	2 7	4 3	3 5	3 0	2 7	4 1	3 5	3 0	2 7	4 0	3 4	3 0	2 7	2 5		
			0 . 6 3	0 . 8	5 2	4 5	4 0	3 6	5 1	4 4	3 9	3 6	4 9	4 3	3 9	3 6	4 8	4 2	3 8	3 6	3 4		
			0 . 5 6	1 . 0	5 7	5 1	4 6	4 2	5 6	5 0	4 6	4 2	5 4	4 9	4 5	4 2	5 3	4 8	4 4	4 2	4 0		
				1 . 2 5	6 1	5 6	5 1	4 8	6 0	5 5	5 1	4 8	5 8	5 4	5 0	4 7	5 7	5 3	5 0	4 7	4 6		
下方投影面積		c m ²	1 . 5	6 4	5 9	5 5	5 2	6 3	5 8	5 5	5 2	6 1	5 7	5 4	5 1	5 9	5 6	5 3	5 1	4 9			
等価発光面積			c m ²	2 . 0	6 8	6 4	6 0	5 7	6 7	6 3	6 0	5 7	6 5	6 1	5 9	5 6	6 3	6 0	5 8	5 6	5 4		
取付高さ	器具間隔最大限		2 . 5	7 0	6 6	6 3	6 1	6 9	6 6	6 3	6 1	6 7	6 4	6 2	6 0	6 5	6 3	6 1	5 9	5 7			
	横方向 (A)		縦方向 (B)	3 . 0	7 1	6 8	6 6	6 3	7 0	6 7	6 5	6 3	6 8	6 6	6 4	6 2	6 7	6 5	6 3	6 1	6 0		
H m	1 . 2 8 H m	1 . 2 8 H m	4 . 0	7 3	7 1	6 9	6 7	7 2	7 0	6 8	6 6	7 0	6 8	6 7	6 5	6 8	6 7	6 6	6 4	6 3			
			5 . 0	7 4	7 2	7 0	6 9	7 3	7 1	7 0	6 8	7 1	7 0	6 8	6 7	7 0	6 8	6 7	6 6	6 4			
			7 . 0	7 5	7 4	7 2	7 1	7 4	7 3	7 2	7 1	7 2	7 1	7 0	6 9	7 1	7 0	6 9	6 8	6 6			
			1 0 . 0	7 6	7 5	7 4	7 3	7 5	7 4	7 3	7 3	7 3	7 3	7 2	7 1	7 2	7 1	7 1	7 0	6 8			

