

屋内照明器具特性	
品番 (品名)	L G B 1 5 4 8 7
光源	LLD5000LCC1 ×1 1140.0 lm
管理番号	K0190419 (0) DR 1
B Z 分類	BZ3 / 0.9 / BZ2

器具効率		94 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	61	51	45	41	60	51	45	41	58	50	44	40	56	49	44	40	39
			0.63	0.8	71	62	56	52	70	62	56	52	68	61	55	52	66	60	55	51	50
			0.56	1.0	77	69	64	60	76	69	64	60	74	68	63	59	72	66	62	59	57
				1.25	82	76	71	67	81	75	70	67	79	74	69	66	77	72	69	66	64
下方投影面積		cm ²		1.5	86	80	75	72	85	79	75	71	82	78	74	71	80	76	73	70	68
			等価発光面積	cm ²	2.0	90	85	81	78	89	84	81	78	86	83	80	77	84	81	79	76
取付 高さ	器具間隔最大限			2.5	93	89	85	82	91	88	85	82	89	86	83	81	87	84	82	80	78
	横方向 (A) 縦方向 (B)			3.0	94	91	88	85	93	90	87	85	91	88	86	84	89	86	84	83	80
H m	1.27 H m	1.27 H m		4.0	96	94	91	89	95	93	90	89	93	91	89	87	91	89	87	86	84
				5.0	97	95	93	92	96	94	93	91	94	92	91	89	92	91	89	88	86
				7.0	99	97	96	94	98	96	95	94	95	94	93	92	93	92	91	91	88
				10.0	100	99	98	97	99	98	97	96	96	96	95	94	94	94	93	92	90

