

屋内照明器具特性	
品番 (品名)	L G B 1 5 4 8 8
光源	L L D 4 0 0 0 L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 8 5 4 9 1 (0) D R 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3

器具効率		7 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 7	0 . 6	4 8	3 9	3 3	2 9	4 7	3 9	3 3	2 9	4 5	3 8	3 3	2 9	4 4	3 7	3 3	2 9	2 8
			0 . 6 3	0 . 8	5 7	4 9	4 3	3 9	5 6	4 8	4 3	3 9	5 4	4 7	4 3	3 9	5 2	4 6	4 2	3 9	3 7
			0 . 5 6	1 . 0	6 3	5 5	5 0	4 6	6 2	5 5	5 0	4 6	6 0	5 4	4 9	4 6	5 8	5 3	4 9	4 6	4 4
				1 . 2 5	6 7	6 1	5 6	5 3	6 6	6 0	5 6	5 2	6 4	5 9	5 5	5 2	6 2	5 8	5 5	5 2	5 0
下方投影面積		c m ²	1 . 5	7 0	6 5	6 0	5 7	6 9	6 4	6 0	5 7	6 7	6 3	5 9	5 6	6 5	6 1	5 8	5 6	5 4	
			2 . 0	7 4	7 0	6 6	6 3	7 3	6 9	6 6	6 3	7 1	6 8	6 5	6 2	6 9	6 6	6 4	6 1	6 0	
取付 高さ	器具間隔最大限		2 . 5	7 7	7 3	7 0	6 7	7 6	7 2	6 9	6 6	7 3	7 1	6 8	6 6	7 2	6 9	6 7	6 5	6 3	
	横方向 (A) 縦方向 (B)		3 . 0	7 8	7 5	7 2	7 0	7 7	7 4	7 1	6 9	7 5	7 3	7 0	6 8	7 3	7 1	6 9	6 7	6 6	
H m	1 . 2 8 H m	1 . 2 8 H m	4 . 0	8 0	7 8	7 5	7 3	7 9	7 7	7 5	7 3	7 7	7 5	7 3	7 2	7 5	7 4	7 2	7 1	6 9	
			5 . 0	8 1	7 9	7 7	7 6	8 0	7 8	7 7	7 5	7 8	7 7	7 5	7 4	7 6	7 5	7 4	7 3	7 1	
			7 . 0	8 3	8 1	8 0	7 8	8 2	8 0	7 9	7 8	8 0	7 8	7 7	7 6	7 8	7 7	7 6	7 5	7 3	
			1 0 . 0	8 4	8 2	8 1	8 0	8 3	8 2	8 1	8 0	8 1	8 0	7 9	7 8	7 9	7 8	7 7	7 7	7 5	

