

屋内照明器具特性	
品番 (品名)	LGB15488
光源	LLD4000MLCE1 ×1 845.0 lm
管理番号	K0185494 (0) DR 1
BZ分類	BZ4/0.7/BZ3

器具効率		72 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	44	36	31	27	43	35	30	27	41	35	30	27	40	34	30	27	25
			0.63	0.8	52	45	40	36	51	44	39	36	49	43	39	36	48	42	38	36	34
			0.56	1.0	57	51	46	42	56	50	46	42	54	49	45	42	53	48	44	42	40
			1.25	61	56	51	48	60	55	51	48	58	54	50	47	57	53	50	47	46	
下方投影面積		cm ²	1.5	64	59	55	52	63	58	55	52	61	57	54	51	59	56	53	51	49	
等価発光面積			2.0	68	64	60	57	67	63	60	57	65	61	59	56	63	60	58	56	54	
取付 高さ	器具間隔最大限			2.5	70	66	63	61	69	66	63	61	67	64	62	60	65	63	61	59	57
	横方向 (A)		縦方向 (B)	3.0	71	68	66	63	70	67	65	63	68	66	64	62	67	65	63	61	60
H m	1.28 H m		1.28 H m	4.0	73	71	69	67	72	70	68	66	70	68	67	65	68	67	66	64	63
				5.0	74	72	70	69	73	71	70	68	71	70	68	67	70	68	67	66	64
				7.0	75	74	72	71	74	73	72	71	72	71	70	69	71	70	69	68	66
				10.0	76	75	74	73	75	74	73	73	73	73	72	71	72	71	71	70	68

