

屋外照明器具特性

品番(品名)	XYT2002R																		
光源	LED2700_70_680 x1 680.0 lm																		
管理番号	K0172103(0)DR1																		
JISC8131-1999 による配光形式																			
器具効率 上方光束 下方光束	100.0 %				直下光度				0.0 cd/1000lm										
	18.4%				最大光度				233.5 cd/1000lm										
鉛直角	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°
=0°鉛直面	0	1	2	4	16	77	135	168	200	233	231	217	196	162	116	89	63	43	34
90°	0	1	2	4	16	77	135	168	200	233	231	217	196	162	116	89	63	43	34
180°	0	1	2	4	16	77	135	168	200	233	231	217	196	162	116	89	63	43	34
270°	0	1	2	4	16	77	135	168	200	233	231	217	196	162	116	89	63	43	34
I _{max} を含む鉛直面	0	1	2	4	16	77	135	168	200	233	231	217	196	162	116	89	63	43	34




道路・トンネル照明率曲線

品番(品名)	XYT2002R	光源	LED2700_70_680 ×1
管理番号	K0172103 (0)DR 1		

————— = 0.0°

H: 取付高さ



歩道側 ← → 車道側