

屋内照明器具特性	
品番 (品名)	L G B 1 5 4 9 3
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0185517 (0) DR 1
B Z 分類	BZ3 / 1.4 / BZ2 / 4.5 / BZ3 / 6.0 / BZ2

器具効率		75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	47	39	33	30	46	38	33	30	44	37	33	29	43	37	33	29	28
			0.63	0.8	55	48	43	39	54	47	43	39	52	46	42	39	51	46	42	39	37
			0.56	1.0	61	54	49	46	60	54	49	46	58	52	49	46	56	52	48	45	44
				1.25	65	59	55	52	64	59	55	52	62	58	54	51	60	56	53	51	49
下方投影面積		cm ²		1.5	68	63	59	56	67	62	58	56	65	61	58	55	63	60	57	55	53
			等価発光面積	cm ²	2.0	71	67	64	61	70	67	64	61	68	65	63	60	67	64	62	60
取付 高さ	器具間隔最大限			2.5	73	70	67	65	72	69	67	64	71	68	66	64	69	67	65	63	61
	横方向 (A) 縦方向 (B)			3.0	75	72	69	67	74	71	69	67	72	70	68	66	70	68	67	65	63
H m	1.21 H m 1.21 H m			4.0	77	74	72	71	76	74	72	70	74	72	70	69	72	71	69	68	66
				5.0	78	76	74	73	77	75	73	72	75	73	72	71	73	72	71	70	68
				7.0	79	77	76	75	78	77	75	74	76	75	74	73	74	73	73	72	70
				10.0	80	79	78	77	79	78	77	76	77	76	75	75	75	75	74	73	71

