

屋内照明器具特性	
品番 (品名)	L G B 1 5 4 9 3
光源	L L D 4 0 0 0 M L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 8 5 5 2 0 (0) D R 1
B Z 分類	B Z 3 / 1 . 4 / B Z 2

器具効率		65 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	41	33	29	26	40	33	29	26	38	32	28	26	37	32	28	25	24
			0.63	0.8	48	41	37	34	47	41	37	34	45	40	37	34	44	39	36	34	32
			0.56	1.0	52	47	43	40	52	46	43	40	50	45	42	39	48	45	42	39	38
				1.25	56	51	48	45	55	51	47	45	54	50	47	44	52	49	46	44	43
下方投影面積		cm ²		1.5	59	54	51	48	58	54	51	48	56	53	50	48	55	52	49	47	46
			等価発光面積	cm ²	2.0	62	58	55	53	61	58	55	53	59	56	54	52	58	55	53	52
取付 高さ	器具間隔最大限			2.5	63	61	58	56	63	60	58	56	61	59	57	55	59	58	56	54	53
	横方向 (A)		縦方向 (B)	3.0	65	62	60	58	64	62	60	58	62	60	59	57	61	59	58	56	55
H m	1.22 H m		1.22 H m	4.0	66	64	63	61	65	64	62	61	64	62	61	60	62	61	60	59	57
				5.0	67	65	64	63	66	65	63	62	65	63	62	61	63	62	61	60	59
				7.0	68	67	66	65	67	66	65	64	66	65	64	63	64	63	63	62	60
				10.0	69	68	67	66	68	67	66	66	66	66	65	65	65	64	64	63	62

