

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 8 8
光源	L L D 4 0 0 0 M L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 8 5 4 9 4 (0) D R 1
B Z 分類	B Z 4 / 0 . 7 / B Z 3

器具効率		72 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束		72 %																					
保守率		良 中 否	0 . 6 7	0 . 6	44	36	31	27	43	35	30	27	41	35	30	27	40	34	30	27	25		
			0 . 6 3	0 . 8	52	45	40	36	51	44	39	36	49	43	39	36	48	42	38	36	34		
			0 . 5 6	1 . 0	57	51	46	42	56	50	46	42	54	49	45	42	53	48	44	42	40		
				1 . 2 5	61	56	51	48	60	55	51	48	58	54	50	47	57	53	50	47	46		
下方投影面積		c m ²	1 . 5	64	59	55	52	63	58	55	52	61	57	54	51	59	56	53	51	49			
等価発光面積			c m ²	2 . 0	68	64	60	57	67	63	60	57	65	61	59	56	63	60	58	56	54		
				2 . 5	70	66	63	61	69	66	63	61	67	64	62	60	65	63	61	59	57		
取付 高さ	器具間隔最大限		3 . 0	71	68	66	63	70	67	65	63	68	66	64	62	67	65	63	61	60			
	横方向 (A)	縦方向 (B)	4 . 0	73	71	69	67	72	70	68	66	70	68	67	65	68	67	66	64	63			
H m	1 . 2 8 H m	1 . 2 8 H m	5 . 0	74	72	70	69	73	71	70	68	71	70	68	67	70	68	67	66	64			
			7 . 0	75	74	72	71	74	73	72	71	72	71	70	69	71	70	69	68	66			
			1 0 . 0	76	75	74	73	75	74	73	73	73	73	72	71	72	71	71	70	68			

