

屋内照明器具特性	
品番 (品名)	NY Y 2 3 0 9 5 K
光源	LED5000_85_1790 x1 1790.0 lm
管理番号	K0164645(0)DB1
BZ分類	BZ5/1.1/BZ4

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 ( X0.01)																ZCM	
保守率	良 中 否	0.77	0.6	5.7	4.5	3.8	3.2	5.6	4.5	3.7	3.2	5.4	4.4	3.7	3.2	5.2	4.3	3.6	3.2	3.0
		0.72	0.8	6.8	5.6	4.8	4.3	6.6	5.6	4.8	4.3	6.3	5.4	4.7	4.3	6.1	5.3	4.7	4.2	4.0
		0.68	1.0	7.4	6.4	5.6	5.1	7.3	6.3	5.6	5.0	7.0	6.1	5.5	5.0	6.7	6.0	5.4	5.0	4.8
			1.25	8.0	7.1	6.4	5.8	7.9	7.0	6.3	5.8	7.6	6.8	6.2	5.7	7.3	6.6	6.1	5.7	5.5
下方投影面積		cm <sup>2</sup>	1.5	8.4	7.6	6.9	6.4	8.3	7.5	6.9	6.4	8.0	7.3	6.7	6.3	7.7	7.1	6.6	6.2	6.0
等価発光面積		cm <sup>2</sup>	2.0	9.0	8.3	7.7	7.2	8.8	8.2	7.6	7.2	8.5	8.0	7.5	7.1	8.3	7.8	7.4	7.0	6.8
取付高さ	器具間隔最大限		2.5	9.4	8.7	8.2	7.8	9.2	8.6	8.2	7.7	8.9	8.4	8.0	7.7	8.6	8.2	7.9	7.6	7.3
	横方向 (A)	縦方向 (B)	3.0	9.6	9.1	8.6	8.2	9.4	9.0	8.5	8.2	9.1	8.7	8.4	8.1	8.9	8.5	8.2	7.9	7.7
Hm	1.25Hm	1.25Hm	4.0	9.9	9.5	9.1	8.8	9.8	9.4	9.0	8.7	9.5	9.1	8.9	8.6	9.2	8.9	8.7	8.5	8.2
			5.0	10.1	9.7	9.4	9.1	9.9	9.6	9.3	9.1	9.7	9.4	9.2	8.9	9.4	9.2	9.0	8.8	8.5
			7.0	10.3	10.0	9.8	9.6	10.2	9.9	9.7	9.5	9.9	9.7	9.5	9.3	9.7	9.5	9.3	9.2	8.9
			10.0	10.5	10.3	10.1	9.9	10.3	10.2	10.0	9.8	10.1	9.9	9.8	9.7	9.8	9.7	9.6	9.5	9.2

