

屋内照明器具特性	
品番 (品名)	XLGB1410
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0185491 (0) DR 1
BZ分類	BZ4/0.7/BZ3

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	48	39	33	29	47	39	33	29	45	38	33	29	44	37	33	29	28
			0.63	0.8	57	49	43	39	56	48	43	39	54	47	43	39	52	46	42	39	37
			0.56	1.0	63	55	50	46	62	55	50	46	60	54	49	46	58	53	49	46	44
				1.25	67	61	56	53	66	60	56	52	64	59	55	52	62	58	55	52	50
下方投影面積		cm ²		1.5	70	65	60	57	69	64	60	57	67	63	59	56	65	61	58	56	54
			等価発光面積	cm ²	2.0	74	70	66	63	73	69	66	63	71	68	65	62	69	66	64	61
取付 高さ	器具間隔最大限			2.5	77	73	70	67	76	72	69	66	73	71	68	66	72	69	67	65	63
	横方向 (A) 縦方向 (B)			3.0	78	75	72	70	77	74	71	69	75	73	70	68	73	71	69	67	66
H m	1.28 H m	1.28 H m		4.0	80	78	75	73	79	77	75	73	77	75	73	72	75	74	72	71	69
				5.0	81	79	77	76	80	78	77	75	78	77	75	74	76	75	74	73	71
				7.0	83	81	80	78	82	80	79	78	80	78	77	76	78	77	76	75	73
				10.0	84	82	81	80	83	82	81	80	81	80	79	78	79	78	78	77	75

