

屋内照明器具特性	
品番 (品名)	XLGB1420
光源	LLD40005CQ1 ×1 845.0 lm
管理番号	K0185501 (0) DR 1
BZ分類	BZ1

器具効率		66 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	51	46	43	41	51	46	43	41	50	46	43	41	49	45	43	41	40
			0.63	0.8	56	52	49	47	56	52	49	47	55	51	49	47	54	51	48	47	46
			0.56	1.0	60	56	53	51	59	55	53	51	58	55	52	51	57	54	52	50	49
				1.25	62	59	56	54	61	58	56	54	60	58	55	54	59	57	55	53	52
下方投影面積 等価発光面積		c m ²		1.5	64	61	59	57	63	60	58	56	62	59	58	56	61	59	57	56	55
				2.0	66	63	61	60	65	63	61	60	64	62	60	59	62	61	60	58	57
				2.5	67	65	63	62	66	64	63	62	65	63	62	61	64	62	61	60	59
				3.0	68	66	65	63	67	66	64	63	66	64	63	62	64	63	62	61	60
H m	0.74 H m	0.74 H m		4.0	69	67	66	65	68	67	66	65	67	66	65	64	65	64	64	63	61
				5.0	69	68	67	66	69	68	67	66	67	66	66	65	66	65	65	64	62
				7.0	70	69	69	68	69	69	68	67	68	67	67	66	66	66	65	65	63
				10.0	71	70	69	69	70	69	69	68	68	68	67	67	67	67	66	66	64

