

屋内照明器具特性																																																																																																																																																																																																							
品番 (品名)		YYY46024M																																																																																																																																																																																																					
光源		LED4000_70_3240 ×1 3240.0 lm																																																																																																																																																																																																					
管理番号		K0181307 (0) DR1																																																																																																																																																																																																					
BZ分類		BZ10																																																																																																																																																																																																					
器具効率 上方光束 下方光束		100 % 100 % 0 %	反射率	天井	80 %				70 %				50 %				30 %				0 %																																																																																																																																																																																		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																																																																																																																																																																		
				床	10 %				10 %				10 %				10 %				0 %																																																																																																																																																																																		
				室指数	照明率 (X0.01) ZCM																																																																																																																																																																																																		
保守率		良 0.69 中 0.67 否 0.63	0.6	43	33	26	22	37	28	23	19	25	19	16	13	14	11	9	8	0																																																																																																																																																																																			
			0.8	51	41	34	29	43	35	30	25	29	24	21	18	17	14	12	11	0																																																																																																																																																																																			
			1.0	56	47	40	35	48	41	35	31	33	28	24	22	19	16	14	13	0																																																																																																																																																																																			
			1.25	61	53	47	42	52	46	40	36	36	31	28	26	20	18	16	15	0																																																																																																																																																																																			
下方投影面積 等価発光面積		cm ² cm ²	1.5	65	57	51	47	56	49	44	40	38	34	31	28	22	20	18	17	0																																																																																																																																																																																			
			2.0	70	63	58	54	60	55	50	47	41	38	35	33	24	22	21	19	0																																																																																																																																																																																			
取付高さ	器具間隔最大限		2.5	73	67	63	59	63	58	54	51	43	40	38	36	25	23	22	21	0																																																																																																																																																																																			
	横方向 (A)	縦方向 (B)	3.0	75	70	66	62	65	61	57	54	44	42	40	38	26	24	23	22	0																																																																																																																																																																																			
H m	0.20H m	0.20H m	4.0	78	74	71	68	67	64	61	59	46	44	43	41	27	26	25	24	0																																																																																																																																																																																			
			5.0	80	76	73	71	68	66	64	61	47	46	44	43	27	27	26	25	0																																																																																																																																																																																			
			7.0	81	79	77	75	70	68	67	65	49	48	46	45	28	28	27	27	0																																																																																																																																																																																			
			10.0	83	81	80	78	72	70	69	68	50	49	48	47	29	29	28	28	0																																																																																																																																																																																			
配光曲線 ランプ光束1000lm A B				直射水平面照度 ランプ光束1000lm <table><tr><td>8.0 lx</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>6.0</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>4.0</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>2.0</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>1.0</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>0.8</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>0.6</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>0.4</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>0.2</td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table> A B																8.0 lx																				6.0																				4.0																				2.0																				1.0																				0.8																				0.6																				0.4																				0.2																			
				8.0 lx																																																																																																																																																																																																			
				6.0																																																																																																																																																																																																			
				4.0																																																																																																																																																																																																			
				2.0																																																																																																																																																																																																			
1.0																																																																																																																																																																																																							
0.8																																																																																																																																																																																																							
0.6																																																																																																																																																																																																							
0.4																																																																																																																																																																																																							
0.2																																																																																																																																																																																																							
				8m 6 4 2 0 2 4 6 8																																																																																																																																																																																																			