

# 屋内照明器具特性

品番 (品名)	XNW7560WW		
光源	LED4000_80_6635 ×1	6635.0 lm	
管理番号	K0172533(0)DB1		
BZ分類	BZ1		

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10		
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 ( X0.01)																ZCM	
保守率	良	0.76	0.6	77	69	64	61	76	69	64	61	74	68	63	60	73	67	63	60	59
	中	0.72	0.8	84	78	73	70	84	77	73	70	82	76	72	69	80	75	72	69	68
	否	0.64	1.0	89	83	79	76	88	83	79	76	86	82	78	75	85	81	77	75	73
下方投影面積	等価発光面積	cm <sup>2</sup>	1.25	93	88	84	81	92	87	84	81	90	86	83	80	88	85	82	80	78
			1.5	96	91	87	85	95	90	87	84	93	89	86	84	91	88	85	83	81
取付高さ	器具間隔最大限		2.0	99	95	92	90	98	94	91	89	96	93	90	88	94	91	89	87	86
	横方向 (A)	縦方向 (B)	2.5	101	98	95	93	100	97	94	92	98	95	93	91	96	94	92	90	88
Hm	0.77Hm	0.77Hm	3.0	102	99	97	95	101	98	96	94	99	97	95	93	97	95	93	92	90
			4.0	104	102	100	98	102	101	99	97	100	99	97	96	98	97	96	95	92
			5.0	105	103	101	100	103	102	100	99	101	100	99	98	99	98	97	96	94
			7.0	106	104	103	102	104	103	102	101	102	101	100	100	100	99	99	98	95
			10.0	106	105	105	104	105	104	104	103	103	102	102	101	101	100	100	99	97

