

屋内照明器具特性	
品番 (品名)	N W C F 5 9 3 1 8
光源	LED3500_70_480 ×1 480.0 l m
管理番号	K0185160 (2) DR 1
B Z 分類	B Z 9

器具効率		100 % 上方光束 50 % 下方光束	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01) Z CM																	
保守率		良 中 否	0.63	0.6	0.6	0.56	0.6	0.8	1.0	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	9.0	10.0	
			44	52	58	64	68	73	77	80	83	86	88	91	4	5	6	7	8	9	10	11
			31	40	46	52	57	64	69	72	77	80	84	88	9	10	11	12	13	14	15	16
			23	31	37	44	49	57	62	66	72	76	80	85	2	3	4	5	6	7	8	9
下方投影面積		cm ²	1.5	68	57	49	42	62	53	45	39	51	44	38	33	41	35	31	27	17		
等価発光面積			2.0	73	64	57	50	67	59	52	47	56	49	44	39	45	40	36	32	21		
取付高さ			2.5	77	69	62	56	71	64	57	52	59	53	48	44	48	43	40	36	24		
器具間隔最大限			3.0	80	72	66	61	73	67	61	56	61	56	52	48	50	46	42	39	26		
H m		0.00 H m	1.85 H m	4.0	83	77	72	67	77	71	67	62	64	60	56	53	53	50	47	44	30	
				5.0	86	80	76	71	79	74	70	66	67	63	60	56	55	52	49	47	32	
				7.0	88	84	80	77	82	78	75	72	69	66	64	61	57	55	53	51	36	
				10.0	91	88	85	82	84	81	79	76	72	69	67	65	60	58	56	54	39	

