

屋内照明器具特性	
品番 (品名)	N W C F 5 9 5 1 6
光源	LED2700_70_170 ×1 170.0 l m
管理番号	K0185155 (0) DR 1
B Z 分類	B Z 1

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	6 2	5 3	4 8	4 4	5 8	5 1	4 6	4 2	5 1	4 6	4 2	3 9	4 5	4 1	3 9	3 7	3 2
			0 . 6 3	0 . 8	6 9	6 1	5 5	5 1	6 5	5 8	5 3	5 0	5 7	5 2	4 8	4 6	5 0	4 6	4 4	4 2	3 6
			0 . 5 6	1 . 0	7 4	6 7	6 1	5 7	6 9	6 3	5 8	5 5	6 1	5 6	5 3	5 0	5 3	5 0	4 7	4 5	3 8
				1 . 2 5	7 8	7 1	6 7	6 3	7 3	6 7	6 3	6 0	6 4	6 0	5 7	5 4	5 5	5 2	5 0	4 9	4 0
下方投影面積		c m ²		1 . 5	8 1	7 5	7 0	6 7	7 6	7 1	6 7	6 3	6 6	6 2	5 9	5 7	5 7	5 4	5 2	5 1	4 1
			等価発光面積		c m ²	2 . 0	8 5	8 0	7 6	7 3	7 9	7 5	7 2	6 9	6 9	6 6	6 3	6 1	5 9	5 7	5 5
取付 高さ	器具間隔最大限		2 . 5	8 7	8 3	7 9	7 6	8 1	7 8	7 5	7 2	7 1	6 8	6 6	6 4	6 0	5 9	5 7	5 6	4 4	
	横方向 (A) 縦方向 (B)			3 . 0	8 9	8 5	8 2	7 9	8 3	8 0	7 7	7 5	7 2	7 0	6 8	6 6	6 1	6 0	5 9	5 8	4 5
H m	0 . 5 2 H m	1 . 0 2 H m	4 . 0	9 1	8 8	8 5	8 3	8 5	8 2	8 0	7 8	7 3	7 2	7 0	6 9	6 2	6 1	6 0	6 0	4 6	
			5 . 0	9 2	9 0	8 8	8 6	8 6	8 4	8 2	8 1	7 4	7 3	7 2	7 0	6 3	6 2	6 2	6 1	4 7	
			7 . 0	9 4	9 2	9 0	8 9	8 7	8 6	8 5	8 3	7 5	7 4	7 3	7 3	6 4	6 3	6 3	6 2	4 7	
			1 0 . 0	9 5	9 3	9 2	9 1	8 8	8 7	8 6	8 5	7 6	7 6	7 5	7 4	6 5	6 4	6 4	6 3	4 8	

